

---

# PyGraphistry Documentation

Graphistry, Inc.

Dec 23, 2022



# CONTENTS

<b>1</b>	<b>graphistry package</b>	<b>3</b>
1.1	graphistry.layout package	3
1.1.1	Subpackages	3
1.1.2	Submodules	3
1.1.3	graphistry.compute.ComputeMixin module	3
1.1.4	Module contents	6
1.2	graphistry.layout package	6
1.2.1	Subpackages	6
1.2.2	Module contents	17
1.3	graphistry.plugins package	17
1.3.1	Subpackages	17
1.3.2	Submodules	17
1.3.3	graphistry.plugins.igraph module	17
1.3.4	Module contents	20
1.4	graphistry.plugins_types package	20
1.4.1	Submodules	20
1.4.2	graphistry.plugins_types.cugraph_types module	20
1.4.3	Module contents	20
1.5	graphistry.plotter module	20
1.6	graphistry.pygraphistry module	20
1.7	graphistry.arrow_uploader module	64
1.8	graphistry.ArrowFileUploader module	66
<b>2</b>	<b>doc</b>	<b>69</b>
2.1	versioneer module	69
<b>3</b>	<b>Indices and tables</b>	<b>71</b>
	<b>Index</b>	<b>73</b>



Quickstart: [Read our tutorial](#)



## GRAPHISTRY PACKAGE

### 1.1 graphistry.layout package

#### 1.1.1 Subpackages

#### 1.1.2 Submodules

#### 1.1.3 graphistry.compute.ComputeMixin module

**class** graphistry.compute.ComputeMixin.**ComputeMixin**(\*args, \*\*kwargs)

Bases: object

**chain**(\*args, \*\*kwargs)

Experimental: Chain a list of operations

Return subgraph of matches according to the list of node & edge matchers

If any matchers are named, add a correspondingly named boolean-valued column to the output

**Parameters** **ops** – List[ASTObject] Various node and edge matchers

**Returns** Plotter

**Return type** *Plotter*

**Example: Find nodes of some type**

```
from graphistry.ast import n

people_nodes_df = g.chain([ n({"type": "person"}) ])._nodes
```

**Example: Find 2-hop edge sequences with some attribute**

```
from graphistry.ast import e_forward

g_2_hops = g.chain([ e_forward({"interesting": True}, hops=2) ])
g_2_hops.plot()
```

**Example: Find any node 1-2 hops out from another node, and label each hop**

```
from graphistry.ast import n, e_undirected
```

(continues on next page)

(continued from previous page)

```

g_2_hops = g.chain([ n({g._node: "a"}), e_undirected(name="hop1"), e_
↪undirected(name="hop2") ])
print('# first-hop edges:', len(g_2_hops._edges[ g_2_hops._edges.hop1 == True_
↪]))

```

**Example: Transaction nodes between two kinds of risky nodes**

```

from graphistry.ast import n, e_forward, e_reverse

g_risky = g.chain([
    n({"risk1": True}),
    e_forward(to_fixed=True),
    n({"type": "transaction", name="hit"},
    e_reverse(to_fixed=True),
    n({"risk2": True})
])
print('# hits:', len(g_risky._nodes[ g_risky._nodes.hit ]))

```

**collapse** (*node*, *attribute*, *column*, *self\_edges=False*, *unwrap=False*, *verbose=False*)Topology-aware collapse by given column attribute starting at *node*

Traverses directed graph from start node *node* and collapses clusters of nodes that share the same property so that topology is preserved.

**Parameters**

- **node** (Union[str, int]) – start *node* to begin traversal
- **attribute** (Union[str, int]) – the given *attribute* to collapse over within *column*
- **column** (Union[str, int]) – the *column* of nodes DataFrame that contains *attribute* to collapse over

:returns: A new Graphistry instance with nodes and edges DataFrame containing collapsed nodes and edges given by column attribute – nodes and edges DataFrames contain six new columns *collapse\_{node | edges}* and *final\_{node | edges}*, while original (node, src, dst) columns are left untouched :rtype: Plottable

**Parameters**

- **self\_edges** (bool) –
- **unwrap** (bool) –
- **verbose** (bool) –

**drop\_nodes** (*nodes*)return *g* with any nodes/edges involving the node id series removed**filter\_edges\_by\_dict** (*\*args*, *\*\*kwargs*)

filter edges to those that match all values in filter\_dict

**filter\_nodes\_by\_dict** (*\*args*, *\*\*kwargs*)

filter nodes to those that match all values in filter\_dict

**get\_degrees** (*col='degree'*, *degree\_in='degree\_in'*, *degree\_out='degree\_out'*)

Decorate nodes table with degree info

Edges must be dataframe-like: pandas, cudf, ...

Parameters determine generated column names

Warning: Self-cycles are currently double-counted. This may change.



**Example: Generate degree columns**

```
edges = pd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'd': ['c', 'c', 'e', 'e']})
g = graphistry.edges(edges, 's', 'd')
print(g._nodes)  # None
g2 = g.get_degrees()
print(g2._nodes)  # pd.DataFrame with 'id', 'degree', 'degree_in',
                  ↪ 'degree_out'
```

**Parameters**

- **col** (str) –
- **degree\_in** (str) –
- **degree\_out** (str) –

**get\_indegrees** (col='degree\_in')

See get\_degrees

**Parameters** **col** (str) –

**get\_outdegrees** (col='degree\_out')

See get\_degrees

**Parameters** **col** (str) –

**get\_topological\_levels** (level\_col='level', allow\_cycles=True, warn\_cycles=True, remove\_self\_loops=True)

Label nodes on column level\_col based on topological sort depth Supports pandas + cudf, using parallelism within each level computation Options: \* allow\_cycles: if False and detects a cycle, throw ValueError, else break cycle by picking a lowest-in-degree node \* warn\_cycles: if True and detects a cycle, proceed with a warning \* remove\_self\_loops: preprocess by removing self-cycles. Avoids allow\_cycles=False, warn\_cycles=True messages.

Example:

```
edges_df = gpd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'd': ['b', 'c', 'e', 'e']})
g = graphistry.edges(edges_df, 's', 'd')
g2 = g.get_topological_levels()
g2._nodes.info() # pd.DataFrame with 1 'id', 'level' |
```

**Parameters**

- **level\_col** (str) –
- **allow\_cycles** (bool) –
- **warn\_cycles** (bool) –
- **remove\_self\_loops** (bool) –

**Return type** Plottable

**hop** (\*args, \*\*kwargs)

Given a graph and some source nodes, return subgraph of all paths within k-hops from the sources

g: Plotter nodes: dataframe with id column matching g.\_node. None signifies all nodes (default). hops: how many hops to consider, if any bound (default 1) to\_fixed\_point: keep hopping until no new nodes are found (ignores hops) direction: 'forward', 'reverse', 'undirected' edge\_match: dict of kv-pairs to exact match (see also: filter\_edges\_by\_dict) source\_node\_match: dict of kv-pairs to match nodes before hopping destination\_node\_match: dict of kv-pairs to match nodes after hopping (including intermediate) return\_as\_wave\_front: Only return the nodes/edges reached, ignoring past ones (primarily for internal use)

**keep\_nodes** (*nodes*)

Limit nodes and edges to those selected by parameter nodes For edges, both source and destination must be in nodes Nodes can be a list or series of node IDs, or a dictionary When a dictionary, each key corresponds to a node column, and nodes will be included when all match

**materialize\_nodes** (*reuse=True, engine='auto'*)

Generate g.\_nodes based on g.\_edges

Uses g.\_node for node id if exists, else 'id'

Edges must be dataframe-like: cudf, pandas, ...

When reuse=True and g.\_nodes is not None, use it

**Example: Generate nodes**

```
edges = pd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'd': ['c', 'c', 'e', 'e']})
g = graphistry.edges(edges, 's', 'd')
print(g._nodes)  # None
g2 = g.materialize_nodes()
print(g2._nodes)  # pd.DataFrame
```

**Parameters**

- **reuse** (bool) –
- **engine** (Union[Engine, Literal['auto']]) –

**Return type** Plottable

**prune\_self\_edges** ()

## 1.1.4 Module contents

## 1.2 graphistry.layout package

### 1.2.1 Subpackages

graphistry.layout.gib package

Submodules

Module contents

graphistry.layout.graph package

Submodules

graphistry.layout.graph.edge module

**class** graphistry.layout.graph.edge.**Edge** (*x, y, w=1, data=None, connect=False*)

Bases: *graphistry.layout.graph.edgeBase.EdgeBase*

A graph edge.

**Attributes**

- **data** (object): an optional payload
- **w** (int): an optional weight associated with the edge (default 1) used by Dijkstra to find min-flow paths.
- **feedback** (bool): whether the Tarjan algorithm has inverted this edge to de-cycle the graph.

**attach()**

Attach this edge to the edge collections of the vertices.

**data:** object

**detach()**

Removes this edge from the edge collections of the vertices.

**feedback:** bool

**w:** int

**graphistry.layout.graph.edgeBase module**

**class** graphistry.layout.graph.edgeBase.**EdgeBase**(x, y)

Bases: object

Base class for edges.

**Attributes**

- **degree** (int): degree of the edge (number of unique vertices).
- **v** (list[Vertex]): list of vertices associated with this edge.

**degree:** int

Is 0 if a loop, otherwise 1.

**graphistry.layout.graph.graph module**

**class** graphistry.layout.graph.graph.**Graph**(vertices=None, edges=None, directed=True)

Bases: object

The graph is stored in disjoint-sets holding each connected component in *components* as a list of graph\_core objects.

**Attributes** **C** (list[GraphBase]): list of graph\_core components.

**Methods** **add\_vertex(v)**: add vertex *v* into the Graph as a new component **add\_edge(e)**: add edge *e* and its vertices into the Graph possibly merging the associated graph\_core components **get\_vertices\_count()**: see **order()** **vertices()**: see **graph\_core** **edges()**: see **graph\_core** **remove\_edge(e)**: remove edge *e* possibly spawning two new cores if the graph\_core that contained *e* gets disconnected. **remove\_vertex(v)**: remove vertex *v* and all its edges. **order()**: the order of the graph (number of vertices) **norm()**: the norm of the graph (number of edges) **deg\_min()**: the minimum degree of vertices **deg\_max()**: the maximum degree of vertices **deg\_avg()**: the average degree of vertices **eps()**: the graph epsilon value (norm/order), average number of edges per vertex. **connected()**: returns True if the graph is connected (i.e. it has only one component). **components()**: returns the list of components

**N**(v, f\_io=0)

**add\_edge**(e)

```
add_edges (edges)
    Parameters edges (List) -
add_vertex (v)
component_class
    alias of graphistry.layout.graph.graphBase.GraphBase
connected ()
deg_avg ()
deg_max ()
deg_min ()
edges ()
eps ()
get_vertex_from_data (data)
get_vertices_count ()
norm ()
order ()
path (x, y, f_io=0, hook=None)
remove_edge (e)
remove_vertex (x)
vertices ()
```

### graphistry.layout.graph.graphBase module

```
class graphistry.layout.graph.graphBase.GraphBase (vertices=None, edges=None, di-
                                                    rected=True)
```

Bases: object

A connected graph of Vertex/Edge objects. A GraphBase is a *component* of a Graph that contains a connected set of Vertex and Edges.

**Attributes:** verticesPoset (Poset[Vertex]): the partially ordered set of vertices of the graph. edgesPoset (Poset[Edge]): the partially ordered set of edges of the graph. loops (set[Edge]): the set of *loop* edges (of degree 0). directed (bool): indicates if the graph is considered *oriented* or not.

**Methods:** vertices(cond=None): generates an iterator over vertices, with optional filter edges(cond=None): generates an iterator over edges, with optional filter matrix(cond=None): returns the associativity matrix of the graph component order(): the order of the graph (number of vertices) norm(): the norm of the graph (number of edges) deg\_min(): the minimum degree of vertices deg\_max(): the maximum degree of vertices deg\_avg(): the average degree of vertices eps(): the graph epsilon value (norm/order), average number of edges per vertex. path(x,y,f\_io=0,hook=None): shortest path between vertices x and y by breadth-first descent, constrained by f\_io direction if provided. The path is returned as a list of Vertex objects. If a *hook* function is provided, it is called at every vertex added to the path, passing the vertex object as argument. roots(): returns the list of *roots* (vertices with no inward edges). leaves(): returns the list of *leaves* (vertices with no outward edges). add\_single\_vertex(v): allow a GraphBase to hold a single vertex. add\_edge(e): add edge e. At least one of its vertex must belong to the graph, the other being added automatically. remove\_edge(e): remove Edge e, asserting that the resulting graph is still connex. remove\_vertex(x): remove Vertex x and all associated edges. dijkstra(x,f\_io=0,hook=None):

shortest weighted-edges paths between  $x$  and all other vertices by dijkstra's algorithm with heap used as priority queue. `get_scs_with_feedback()`: returns the set of strongly connected components ("scs") by using Tarjan algorithm. These are maximal sets of vertices such that there is a path from each vertex to every other vertex. The algorithm performs a DFS from the provided list of root vertices. A cycle is of course a strongly connected component, but a strongly connected component can include several cycles. The Feedback Acyclic Set of edge to be removed/reversed is provided by marking the edges with a "feedback" flag. Complexity is  $O(V+E)$ . `partition()`: returns a *partition* of the connected graph as a list of lists. `neighbors(v)`: returns neighbours of a vertex  $v$ .

**N** ( $v, f\_io=0$ )

**add\_edge** ( $e$ )

**add\_single\_vertex** ( $v$ )

**complement** ( $G$ )

**constant\_function** ( $value$ )

**contract** ( $e$ )

**deg\_avg** ()

**deg\_max** ()

**deg\_min** ()

**dft** ( $start\_vertex=None$ )

**dijkstra** ( $x, f\_io=0, hook=None$ )

**edges** ( $cond=None$ )

**eps** ()

**get\_scs\_with\_feedback** ( $roots=None$ )

Minimum FAS algorithm (feedback arc set) creating a DAG.

**Parameters** **roots** –

**Returns**

**leaves** ()

**matrix** ( $cond=None$ )

This associativity matrix is like the adjacency matrix but antisymmetric.

**Parameters** **cond** – same as the condition function in `vertices()`.

**Returns** array

**norm** ()

The size of the edge poset.

**order** ()

**partition** ()

**path** ( $x, y, f\_io=0, hook=None$ )

**remove\_edge** ( $e$ )

**remove\_vertex** ( $x$ )

```
roots ()
spans (vertices)
union_update (G)
vertices (cond=None)
```

### graphistry.layout.graph.vertex module

```
class graphistry.layout.graph.vertex.Vertex (data=None)
    Bases: graphistry.layout.graph.vertexBase.VertexBase
```

Vertex class enhancing a VertexBase with graph-related features.

**Attributes** component (GraphBase): the component of connected vertices that contains this vertex. By default, a vertex belongs no component but when it is added in a graph, c points to the connected component in this graph. data (object) : an object associated with the vertex.

**property index**

### graphistry.layout.graph.vertexBase module

```
class graphistry.layout.graph.vertexBase.VertexBase
    Bases: object
```

Base class for vertices.

**Attributes** e (list[Edge]): list of edges associated with this vertex.

**Methods** degree() : degree of the vertex (number of edges). e\_in() : list of edges directed toward this vertex. e\_out(): list of edges directed outward this vertex. e\_dir(int): either e\_in, e\_out or all edges depending on provided direction parameter (>0 means outward). neighbors(f\_io=0): list of neighbor vertices in all directions (default) or in filtered f\_io direction (>0 means outward). e\_to(v): returns the Edge from this vertex directed toward vertex v. e\_from(v): returns the Edge from vertex v directed toward this vertex. e\_with(v): return the Edge with both this vertex and vertex v detach(): removes this vertex from all its edges and returns this list of edges.

```
degree ()
detach ()
e_dir (dir)
e_from (x)
e_in ()
e_out ()
e_to (y)
e_with (v)
neighbors (direction=0)
    Returns the neighbors of this vertex.
```

**Parameters direction –**

- 0: parent and children
- -1: parents

- +1: children

**Returns** list of vertices

## Module contents

### graphistry.layout.sugiyama package

#### Submodules

#### graphistry.layout.sugiyama.sugiyamaLayout module

**class** graphistry.layout.sugiyama.sugiyamaLayout.**SugiyamaLayout** (*g*)

Bases: object

The classic Sugiyama layout aka layered layout.

- See [https://en.wikipedia.org/wiki/Layered\\_graph\\_drawing](https://en.wikipedia.org/wiki/Layered_graph_drawing)
- Excellent explanation: <https://www.youtube.com/watch?v=Z0RGCWxvCxA>

#### Attributes

- **dirvh (int): the current alignment state for alignment policy:** dirvh=0 -> dirh=+1, dirv=-1: leftmost upper dirvh=1 -> dirh=-1, dirv=-1: rightmost upper dirvh=2 -> dirh=+1, dirv=+1: leftmost lower dirvh=3 -> dirh=-1, dirv=+1: rightmost lower
- order\_iter (int): the default number of layer placement iterations
- order\_attr (str): set attribute name used for layer ordering
- xspace (int): horizontal space between vertices in a layer
- yspace (int): vertical space between layers
- dw (int): default width of a vertex
- dh (int): default height of a vertex
- g (GraphBase): the graph component reference
- layers (list[sugiyama.layer.Layer]): the list of layers
- layoutVertices (dict): associate vertex (possibly dummy) with their sugiyama attributes
- ctrl (dict): associate edge with all its vertices (including dummies)
- dag (bool): the current acyclic state
- init\_done (bool): True if things were initialized

#### Example

```
g = nx.generators.connected_watts_strogatz_graph(1000, 2, 0.3)
# render
SugiyamaLayout.draw(g)
# positions
positions_dictionary = SugiyamaLayout.arrange(g)
```

**Parameters** *g* (*GraphBase*) –

```
static arrange (obj, iteration_count=1.5, source_column='source', target_column='target',  
                layout_direction=0, topological_coordinates=False, root=None, in-  
                clude_levels=False)
```

Returns the positions from a Sugiyama layout iteration.

#### Parameters

- **layout\_direction** –
  - 0: top-to-bottom
  - 1: right-to-left
  - 2: bottom-to-top
  - 3: left-to-right
- **obj** – can be a Sugiyama graph or a Pandas frame.
- **iteration\_count** – increase the value for diminished crossings
- **source\_column** – if a Pandas frame is given, the name of the column with the source of the edges
- **target\_column** – if a Pandas frame is given, the name of the column with the target of the edges
- **topological\_coordinates** – whether to use coordinates with the x-values in the [0,1] range and the y-value equal to the layer index.
- **include\_levels** – whether the tree-level is included together with the coordinates. If so, you get a triple (x,y,level).
- **root** – optional list of roots.

**Returns** a dictionary of positions.

**Parameters** **obj** (Union[DataFrame, *Graph*]) –

**create\_dummies** (*e*)

Creates and defines all dummy vertices for edge *e*.

**ctrls:** Dict [*graphistry.layout.graph.vertex.Vertex*, *graphistry.layout.utils.layoutVert*

*property dirh*

*property dirv*

*property dirvh*

**draw\_step** ()

Iterator that computes all vertices coordinates and edge routing after just one step (one layer after the other from top to bottom to top). Use it only for “animation” or debugging purpose.

**dummyctrl** (*r*, *control\_vertices*)

Creates a DummyVertex at layer *r* inserted in the ctrl dict of the associated edge and layer.

#### Arguments

- *r* (int): layer value
- *ctrl* (dict): the edge’s control vertices

**Returns** *sugiyama.DummyVertex* : the created DummyVertex.

```
static ensure_root_is_vertex (g, root)
```



Turns the given list of roots (names or data) to actual vertices in the given graph.

#### Parameters

- **g** (*Graph*) – the graph wherein the given roots names are supposed to be
- **root** (*object*) – the data or the vertex

**Returns** the list of vertices to use as roots

**find\_nearest\_layer** (*start\_vertex*)

**static graph\_from\_pandas** (*df*, *source\_column='source'*, *target\_column='target'*)

**static has\_cycles** (*obj*, *source\_column='source'*, *target\_column='target'*)

**Parameters** *obj* (*Union[DataFrame, Graph]*) –

**initialize** (*root=None*)

Initializes the layout algorithm.

#### Parameters:

- **root** (*Vertex*): a vertex to be used as root

**layers:** *List[graphistry.layout.utils.layer.Layer]*

**layout** (*iteration\_count=1.5*, *topological\_coordinates=False*, *layout\_direction=0*)

Compute every node coordinates after converging to optimal ordering by N rounds, and finally perform the edge routing.

**Parameters** *topological\_coordinates* – whether to use ([0,1], layer index) coordinates

**layoutVertices**

The map from vertex to LayoutVertex.

**layout\_edges** ()

Basic edge routing applied only for edges with dummy points. Enhanced edge routing can be performed by using the appropriate

**ordering\_step** (*oneway=False*)

iterator that computes all vertices ordering in their layers (one layer after the other from top to bottom, to top again unless oneway is True).

**set\_coordinates** ()

Computes all vertex coordinates using Brandes & Kopf algorithm. See <https://www.semanticscholar.org/paper/Fast-and-Simple-Horizontal-Coordinate-Assignment-Brandes-Kopf/69cb129a8963b21775d6382d15b0b447b01eb1f8>

**set\_topological\_coordinates** (*layout\_direction=0*)

**xspace:** *int*

**yspace:** *int*

## Module contents

### graphistry.layout.utils package

#### Submodules

#### graphistry.layout.utils.dummyVertex module

**class** graphistry.layout.utils.dummyVertex.**DummyVertex** (*r=None*)

Bases: *graphistry.layout.utils.layoutVertex.LayoutVertex*

A DummyVertex is used for edges that span over several layers, it's inserted in every inner layer.

#### Attributes

- **view** (viewclass): since a DummyVertex is acting as a Vertex, it must have a view.
- **ctrl** (list[\_sugiyama\_attr]): the list of associated dummy vertices.

**inner** (*direction*)

True if a neighbor in the given direction is *dummy*.

**neighbors** (*direction*)

Reflect the Vertex method and returns the list of adjacent vertices (possibly dummy) in the given direction.

:type direction: int :param direction: +1 for the next layer (children) and -1 (parents) for the previous

#### graphistry.layout.utils.geometry module

graphistry.layout.utils.geometry.**angle\_between\_vectors** (*p1, p2*)

graphistry.layout.utils.geometry.**lines\_intersection** (*xy1, xy2, xy3, xy4*)

Returns the intersection of two lines.

graphistry.layout.utils.geometry.**new\_point\_at\_distance** (*pt, distance, angle*)

graphistry.layout.utils.geometry.**rectangle\_point\_intersection** (*rec, p*)

Returns the intersection point between the Rectangle (w,h) that characterize the rec object and the line that goes from the recs' object center to the 'p' point.

graphistry.layout.utils.geometry.**set\_round\_corner** (*e, pts*)

graphistry.layout.utils.geometry.**setcurve** (*e, pts, tgs=None*)

Returns the spline curve that path through the list of points P. The spline curve is a list of cubic bezier curves (nurbs) that have matching tangents at their extreme points. The method considered here is taken from "The NURBS book" (Les A. Piegl, Wayne Tiller, Springer, 1997) and implements a local interpolation rather than a global interpolation.

**Args:** e: pts: tgs:

Returns:

graphistry.layout.utils.geometry.**size\_median** (*recs*)

graphistry.layout.utils.geometry.**tangents** (*P, n*)

## graphistry.layout.utils.layer module

**class** graphistry.layout.utils.layer.**Layer** (*iterable=()*,/)

Bases: list

Layer is where Sugiyama layout organises vertices in hierarchical lists. The placement of a vertex is done by the Sugiyama class, but it highly relies on the *ordering* of vertices in each layer to reduce crossings. This ordering depends on the neighbors found in the upper or lower layers.

**Attributes:** layout (SugiyamaLayout): a reference to the sugiyama layout instance that contains this layer upper (Layer): a reference to the *upper* layer (layer-1) lower (Layer): a reference to the *lower* layer (layer+1) crossings (int) : number of crossings detected in this layer

**Methods:** setup (layout): set initial attributes values from provided layout nextlayer(): returns *next* layer in the current layout's direction parameter. prevlayer(): returns *previous* layer in the current layout's direction parameter. order(): compute *optimal* ordering of vertices within the layer.

**crossings** = None

**layout** = None

**lower** = None

**neighbors** (v)

neighbors refer to upper/lower adjacent nodes. Note that v.neighbors() provides neighbors of v in the graph, while this method provides the Vertex and DummyVertex adjacent to v in the upper or lower layer (depending on layout.dirv state).

**nextlayer** ()

**order** ()

**prevlayer** ()

**setup** (layout)

**upper** = None

## graphistry.layout.utils.layoutVertex module

**class** graphistry.layout.utils.layoutVertex.**LayoutVertex** (*layer=None*,  
*is\_dummy=0*)

Bases: object

The Sugiyama layout adds new attributes to vertices. These attributes are stored in an internal `_sugimyama_vertex_attr` object.

**Attributes:** layer (int): layer number dummy (0/1): whether the vertex is a dummy pos (int): the index of the vertex within the layer x (list(float)): the list of computed horizontal coordinates of the vertex bar (float): the current barycenter of the vertex

**Parameters** **layer** (Optional[int]) –

### graphistry.layout.utils.poset module

**class** graphistry.layout.utils.poset.**Poset** (*collection=[]*)

Bases: object

Poset class implements a set but allows to integrate over the elements in a deterministic way and to get specific objects in the set. Membership operator defaults to comparing `__hash__` of objects but Poset allows to check for `__cmp__`/`__eq__` membership by using `contains__cmp__(obj)`

**add** (*obj*)

**contains\_\_cmp\_\_** (*obj*)

**copy** ()

**deepcopy** ()

**difference** (\**args*)

**get** (*obj*)

**index** (*obj*)

**intersection** (\**args*)

**issubset** (*other*)

**issuperset** (*other*)

**remove** (*obj*)

**symmetric\_difference** (\**args*)

**union** (*other*)

**update** (*other*)

### graphistry.layout.utils.rectangle module

**class** graphistry.layout.utils.rectangle.**Rectangle** (*w=1, h=1*)

Bases: object

Rectangular region.

### graphistry.layout.utils.routing module

**class** graphistry.layout.utils.routing.**EdgeViewer**

Bases: object

**setpath** (*pts*)

graphistry.layout.utils.routing.**route\_with\_lines** (*e, pts*)

Basic edge routing with lines. The layout pass has already provided to list of points through which the edge shall be drawn. We just compute the position where to adjust the tail and head.

graphistry.layout.utils.routing.**route\_with\_rounded\_corners** (*e, pts*)

graphistry.layout.utils.routing.**route\_with\_splines** (*e, pts*)

Enhanced edge routing where ‘corners’ of the above polyline route are rounded with a Bezier curve.

## Module contents

### 1.2.2 Module contents

## 1.3 graphistry.plugins package

### 1.3.1 Subpackages

### 1.3.2 Submodules

### 1.3.3 graphistry.plugins.igraph module

`graphistry.plugins.igraph.compute_igraph`(*self*, *alg*, *out\_col=None*, *directed=None*, *use\_vids=False*, *params={}*)

Enrich or replace graph using igraph methods

#### Parameters

- **alg** (*str*) – Name of an igraph.Graph method like *pagerank*
- **out\_col** (*Optional[str]*) – For algorithms that generate a node attribute column, *out\_col* is the desired output column name. When *None*, use the algorithm’s name. (default *None*)
- **directed** (*Optional[bool]*) – During the to\_igraph conversion, whether to be directed. If *None*, try directed and then undirected. (default *None*)
- **use\_vids** (*bool*) – During the to\_igraph conversion, whether to interpret IDs as igraph vertex IDs (non-negative integers) or arbitrary values (*False*, default)
- **params** (*dict*) – Any named parameters to pass to the underlying igraph method

**Returns** Plotter

**Return type** *Plotter*

#### Example: Pagerank

```
:: import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['c','c','e','e']})
g = graphistry.edges(edges, 's', 'd')
g2 = g.compute_igraph('pagerank')
assert 'pagerank' in g2._nodes.columns
```

#### Example: Pagerank with custom name

```
:: import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['c','c','e','e']})
g = graphistry.edges(edges, 's', 'd')
g2 = g.compute_igraph('pagerank', out_col='my_pr')
assert 'my_pr' in g2._nodes.columns
```

#### Example: Pagerank on an undirected

```
:: import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['c','c','e','e']})
g = graphistry.edges(edges, 's', 'd')
g2 = g.compute_igraph('pagerank', directed=False)
assert 'pagerank' in g2._nodes.columns
```

#### Example: Pagerank with custom parameters

```
:: import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['c','c','e','e']})
g = graphistry.edges(edges, 's', 'd')
g2 = g.compute_igraph('pagerank', params={'damping': 0.85})
assert 'pagerank' in g2._nodes.columns
```

**Parameters** *self* (Plottable) –

```
graphistry.plugins.igraph.from_igraph(self,          ig,          node_attributes=None,
                                         edge_attributes=None,      load_nodes=True,
                                         load_edges=True, merge_if_existing=True)
```

Convert igraph object into Plotter

If base *g* has *\_node*, *\_source*, *\_destination* definitions, use them

When *merge\_if\_existing* with preexisting nodes/edges df and shapes match *ig*, combine attributes

For *merge\_if\_existing* to work with edges, must set *g.\_edge* and have corresponding edge index attribute in *igraph.Graph*

**Parameters**

- **ig** (*igraph*) – Source igraph object
- **node\_attributes** (*Optional[List[str]]*) – Subset of node attributes to load; None means all (default)
- **edge\_attributes** (*Optional[List[str]]*) – Subset of edge attributes to load; None means all (default)
- **load\_nodes** (*bool*) – Whether to load nodes dataframe (default True)
- **load\_edges** (*bool*) – Whether to load edges dataframe (default True)
- **merge\_if\_existing** (*bool*) – Whether to merge with existing node/edge dataframes (default True)
- **merge\_if\_existing** – bool

**Returns** Plotter

**Return type** *Plotter*

**Example: Convert from igraph, including all node/edge properties**

```
:: import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'd': ['b', 'c', 'd', 'e'], 'v': [101, 102, 103, 104]})
g = graphistry.edges(edges, 's', 'd').materialize_nodes().get_degrees()
assert 'degree' in g._nodes.columns
g2 = g.from_igraph(g.to_igraph())
assert len(g2._nodes.columns) == len(g._nodes.columns)
```

**Example: Enrich from igraph, but only load in 1 node attribute**

```
:: import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'd': ['b', 'c', 'd', 'e'], 'v': [101, 102, 103, 104]})
g = graphistry.edges(edges, 's', 'd').materialize_nodes().get_degree()
assert 'degree' in g._nodes
ig = g.to_igraph(include_nodes=False)
assert 'degree' not in ig.vs
ig.vs['pagerank'] = ig.pagerank()
g2 = g.from_igraph(ig, load_edges=False, node_attributes=[g._node, 'pagerank'])
assert 'pagerank' in g2._nodes
assert 'degree' in g2._nodes
```

```
graphistry.plugins.igraph.layout_igraph(self, layout, directed=None, use_vids=False,
                                         bind_position=True, x_out_col='x', y_out_col='y',
                                         play=0, params={})
```

Compute graph layout using igraph algorithm. For a list of layouts, see *layout\_algs* or *igraph* documentation.

**Parameters**

- **layout** (*str*) – Name of an *igraph.Graph.layout* method like *sugiyama*
- **directed** (*Optional[bool]*) – During the *to\_igraph* conversion, whether to be directed. If None, try directed and then undirected. (default None)

- **use\_vids** (*bool*) – Whether to use igraph vertex ids (non-negative integers) or arbitrary node ids (False, default)
- **bind\_position** (*bool*) – Whether to call bind(point\_x=, point\_y=) (default True)
- **x\_out\_col** (*str*) – Attribute to write x position to. (default 'x')
- **y\_out\_col** (*str*) – Attribute to write x position to. (default 'y')
- **play** (*Optional[str]*) – If defined, set settings(url\_params={'play': play}). (default 0)
- **params** (*dict*) – Any named parameters to pass to the underlying igraph method

**Returns** Plotter

**Return type** *Plotter*

#### Example: Sugiyama layout

```
:: import graphistry, pandas as pd edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['b','c','d','e']}) g =
graphistry.edges(edges, 's', 'd') g2 = g.layout_igraph('sugiyama') assert 'x' in g2._nodes g2.plot()
```

#### Example: Change which column names are generated

```
:: import graphistry, pandas as pd edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['b','c','d','e']})
g = graphistry.edges(edges, 's', 'd') g2 = g.layout_igraph('sugiyama', x_out_col='my_x',
y_out_col='my_y') assert 'my_x' in g2._nodes assert g2._point_x == 'my_x' g2.plot()
```

#### Example: Pass parameters to layout methods - Sort nodes by degree

```
:: import graphistry, pandas as pd edges = pd.DataFrame({'s': ['a','b','c','d'], 'd': ['b','c','d','e']}) g
= graphistry.edges(edges, 's', 'd') g2 = g.get_degrees() assert 'degree' in g._nodes.columns g3 =
g.layout_igraph('sugiyama', params={'layers': 'degree'}) g3.plot()
```

**Parameters** **self** (Plottable) –

```
graphistry.plugins.igraph.to_igraph(self, directed=True, include_nodes=True,
node_attributes=None, edge_attributes=None,
use_vids=False)
```

Convert current item to igraph Graph . See examples in from\_igraph.

**Parameters**

- **directed** (*bool*) – Whether to create a directed graph (default True)
- **include\_nodes** (*bool*) – Whether to ingest the nodes table, if it exists (default True)
- **node\_attributes** (*Optional[List[str]]*) – Which node attributes to load, None means all (default None)
- **edge\_attributes** (*Optional[List[str]]*) – Which edge attributes to load, None means all (default None)
- **use\_vids** (*bool*) – Whether to interpret IDs as igraph vertex IDs, which must be non-negative integers (default False)
- **self** (Plottable) –

### 1.3.4 Module contents

## 1.4 graphistry.plugins\_types package

### 1.4.1 Submodules

### 1.4.2 graphistry.plugins\_types.cugraph\_types module

### 1.4.3 Module contents

## 1.5 graphistry.plotter module

```
class graphistry.plotter.Plotter(*args, **kwargs)
    Bases: graphistry.gremlin.CosmosMixin, graphistry.gremlin.
    NeptuneMixin, graphistry.gremlin.GremlinMixin, graphistry.embed_utils.
    HeterographEmbedModuleMixin, graphistry.text_utils.SearchToGraphMixin,
    graphistry.dgl_utils.DGLGraphMixin, graphistry.umap_utils.UMAPMixin,
    graphistry.feature_utils.FeatureMixin, graphistry.compute.conditional.
    ConditionalMixin, graphistry.layouts.LayoutsMixin, graphistry.compute.
    ComputeMixin.ComputeMixin, graphistry.PlotterBase.PlotterBase, object
```

## 1.6 graphistry.pygraphistry module

```
class graphistry.pygraphistry.NumpyJSONEncoder(*, skipkeys=False, ensure_ascii=True,
    check_circular=True, allow_nan=True,
    sort_keys=False, indent=None, separa-
    tors=None, default=None)
```

Bases: `json.encoder.JSONEncoder`

**default** (*obj*)

Implement this method in a subclass such that it returns a serializable object for `o`, or calls the base implementation (to raise a `TypeError`).

For example, to support arbitrary iterators, you could implement default like this:

```
def default(self, o):
    try:
        iterable = iter(o)
    except TypeError:
        pass
    else:
        return list(iterable)
    # Let the base class default method raise the TypeError
    return JSONEncoder.default(self, o)
```

```
class graphistry.pygraphistry.PyGraphistry
```

Bases: `object`

**static addStyle** (*bg=None, fg=None, logo=None, page=None*)

Creates a base plotter with some style settings.

For parameters, see `plotter.addStyle`.



**Returns** Plotter

**Return type** *Plotter*

#### Example

```
import graphistry
graphistry.addStyle(bg={'color': 'black'})
```

**static api\_key** (*value=None*)

Set or get the API key. Also set via environment variable GRAPHISTRY\_API\_KEY.

**static api\_token** (*value=None*)

Set or get the API token. Also set via environment variable GRAPHISTRY\_API\_TOKEN.

**static api\_token\_refresh\_ms** (*value=None*)

Set or get the API token refresh interval in milliseconds. None and 0 interpreted as no refreshing.

**static api\_version** (*value=None*)

Set or get the API version: 1 for 1.0 (deprecated), 3 for 2.0. Setting api=2 (protobuf) fully deprecated from the PyGraphistry client. Also set via environment variable GRAPHISTRY\_API\_VERSION.

**static authenticate** ()

Authenticate via already provided configuration (api=1,2). This is called once automatically per session when uploading and rendering a visualization. In api=3, if token\_refresh\_ms > 0 (defaults to 10min), this starts an automatic refresh loop. In that case, note that a manual .login() is still required every 24hr by default.

**static bind** (*node=None, source=None, destination=None, edge\_title=None, edge\_label=None, edge\_color=None, edge\_weight=None, edge\_icon=None, edge\_size=None, edge\_opacity=None, edge\_source\_color=None, edge\_destination\_color=None, point\_title=None, point\_label=None, point\_color=None, point\_weight=None, point\_icon=None, point\_size=None, point\_opacity=None, point\_x=None, point\_y=None*)

Create a base plotter.

Typically called at start of a program. For parameters, see `plotter.bind()` .

**Returns** Plotter

**Return type** *Plotter*

#### Example

```
import graphistry
g = graphistry.bind()
```

**static bolt** (*driver=None*)

**Parameters** **driver** – Neo4j Driver or arguments for GraphDatabase.driver({...})

**Returns** Plotter w/neo4j

Call this to create a Plotter with an overridden neo4j driver.

#### Example

```
import graphistry
g = graphistry.bolt({ server: 'bolt://...', auth: ('<username>', '
↪<password>') })
```

```
import neo4j
import graphistry

driver = neo4j.GraphDatabase.driver(...)

g = graphistry.bolt(driver)
```

**static** `certificate_validation` (*value=None*)

Enable/Disable SSL certificate validation (True, False). Also set via environment variable GRAPHISTRY\_CERTIFICATE\_VALIDATION.

**static** `client_protocol_hostname` (*value=None*)

Get/set the client protocol+hostname for when display urls (distinct from uploading). Also set via environment variable GRAPHISTRY\_CLIENT\_PROTOCOL\_HOSTNAME. Defaults to hostname and no protocol (reusing environment protocol)

**static** `cosmos` (*COSMOS\_ACCOUNT=None*, *COSMOS\_DB=None*, *COS-*  
*MOS\_CONTAINER=None*, *COSMOS\_PRIMARY\_KEY=None*, *gremlin\_client=None*)

Provide credentials as arguments, as environment variables, or by providing a gremlinpython client Environment variable names are the same as the constructor argument names If no client provided, create (connect)

#### Parameters

- **COSMOS\_ACCOUNT** (Optional[str]) – cosmos account
- **COSMOS\_DB** (Optional[str]) – cosmos db name
- **COSMOS\_CONTAINER** (Optional[str]) – cosmos container name
- **COSMOS\_PRIMARY\_KEY** (Optional[str]) – cosmos key
- **gremlin\_client** (Optional[Any]) – optional prebuilt client

**Return type** *Plotter*

**Returns** Plotter with data from a cypher query. This call binds *source*, *destination*, and *node*.

#### Example: Login and plot

```
import graphistry
(graphistry
 .cosmos(
     COSMOS_ACCOUNT='a',
     COSMOS_DB='b',
     COSMOS_CONTAINER='c',
     COSMOS_PRIMARY_KEY='d')
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**static** `cypher` (*query*, *params={}*)

#### Parameters

- **query** – a cypher query
- **params** – cypher query arguments

**Returns** Plotter with data from a cypher query. This call binds *source*, *destination*, and *node*.

Call this to immediately execute a cypher query and store the graph in the resulting Plotter.

```
import graphistry
g = graphistry.bolt({ query='MATCH (a)-[r:PAYMENT]->(b) WHERE r.USD > 7000 AND r.USD < 10000 RETURN r ORDER BY r.USD DESC', params={
    "AccountId": 10 })
```

**static description** (*description*)

Upload description

**Parameters** *description* (*str*) – Upload description

**static drop\_graph** ()

Remove all graph nodes and edges from the database

**Return type** *Plotter*

**static edges** (*edges*, *source=None*, *destination=None*, *\*args*, *\*\*kwargs*)

Specify edge list data and associated edge attribute values. If a callable, will be called with current Plotter and whatever positional+named arguments

**Parameters** *edges* (*Pandas dataframe, NetworkX graph, or IGraph graph*) – Edges and their attributes, or transform from Plotter to edges

**Returns** Plotter

**Return type** *Plotter*

#### Example

```
import graphistry
df = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
graphistry
    .bind(source='src', destination='dst')
    .edges(df)
    .plot()
```

#### Example

```
import graphistry
df = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
graphistry
    .edges(df, 'src', 'dst')
    .plot()
```

#### Example

```
:: import graphistry
```

```
def sample_edges(g, n): return g._edges.sample(n)
```

```
df = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
```

```
graphistry .edges(df, 'src', 'dst') .edges(sample_edges, n=2) .edges(sample_edges, None,
    None, 2) # equivalent .plot()
```

**static encode\_edge\_badge** (*column*, *position="TopRight"*, *categorical\_mapping=None*, *continuous\_binning=None*, *default\_mapping=None*, *comparator=None*, *color=None*, *bg=None*, *fg=None*, *for\_current=False*, *for\_default=True*, *as\_text=None*, *blend\_mode=None*, *style=None*, *border=None*, *shape=None*)

```
static encode_edge_color (column,                palette=None,                as_categorical=None,
                           as_continuous=None,      categorical_mapping=None,      de-
                           fault_mapping=None, for_default=True, for_current=False)
```

Set edge color with more control than `bind()`

#### Parameters

- **column** (*str*) – Data column name
- **palette** (*Optional[list]*) – Optional list of color-like strings. Ex: ["black", "#FF0", "rgb(255,255,255)"]. Used as a gradient for continuous and round-robin for categorical.
- **as\_categorical** (*Optional[bool]*) – Interpret column values as categorical. Ex: Uses palette via round-robin when more values than palette entries.
- **as\_continuous** (*Optional[bool]*) – Interpret column values as continuous. Ex: Uses palette for an interpolation gradient when more values than palette entries.
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to color-like strings. Ex: {"car": "red", "truck": "#000"}
- **default\_mapping** (*Optional[str]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping="gray".
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.

**Returns** Plotter

**Return type** *Plotter*

**Example:** See `encode_point_color`

```
static encode_edge_icon (column,  categorical_mapping=None,  continuous_binning=None,
                           default_mapping=None,  comparator=None,  for_default=True,
                           for_current=False, as_text=False, blend_mode=None, style=None,
                           border=None, shape=None)
```

Set edge icon with more control than `bind()`. Values from Font Awesome 4 such as "laptop": <https://fontawesome.com/v4.7.0/icons/>

#### Parameters

- **column** (*str*) – Data column name
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to icon name strings. Ex: {"toyota": 'car', "ford": 'truck'}
- **default\_mapping** (*Optional[Union[int, float]]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping=50.
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.
- **as\_text** (*Optional[bool]*) – Values should instead be treated as raw strings, instead of icons and images. (Default False.)
- **blend\_mode** (*Optional[str]*) – CSS blend mode

- **style** (*Optional[dict]*) – CSS filter properties - opacity, saturation, luminosity, grayscale, and more
- **border** (*Optional[dict]*) – Border properties - ‘width’, ‘color’, and ‘stroke’

Returns Plotter

Return type *Plotter*

**Example: Set a string column of icons for the edge icons, same as `bind(edge_icon='my_column')`**

```
g2a = g.encode_edge_icon('my_icons_column')
```

**Example: Map specific values to specific icons, including with a default**

```
g2a = g.encode_edge_icon('brands', categorical_mapping={'toyota': 'car',
↳ 'ford': 'truck'})
g2b = g.encode_edge_icon('brands', categorical_mapping={'toyota': 'car',
↳ 'ford': 'truck'}, default_mapping='question')
```

**Example: Map countries to abbreviations**

```
g2a = g.encode_edge_icon('country_abbrev', as_text=True)
g2b = g.encode_edge_icon('country', categorical_mapping={'England': 'UK',
↳ 'America': 'US'}, default_mapping='')
```

**Example: Border**

```
g2b = g.encode_edge_icon('country', border={'width': 3, color: 'black',
↳ 'stroke': 'dashed'}, 'categorical_mapping={'England': 'UK', 'America':
↳ 'US'})
```

```
static encode_point_badge(column, position='TopRight', categorical_mapping=None,
continuous_binning=None, default_mapping=None, comparator=None, color=None, bg=None, fg=None, for_current=False,
for_default=True, as_text=None, blend_mode=None, style=None,
border=None, shape=None)
```

```
static encode_point_color(column, palette=None, as_categorical=None,
as_continuous=None, categorical_mapping=None, default_mapping=None, for_default=True, for_current=False)
```

Set point color with more control than `bind()`

#### Parameters

- **column** (*str*) – Data column name
- **palette** (*Optional[list]*) – Optional list of color-like strings. Ex: [“black”, “#FF0”, “rgb(255,255,255)” ]. Used as a gradient for continuous and round-robin for categorical.
- **as\_categorical** (*Optional[bool]*) – Interpret column values as categorical. Ex: Uses palette via round-robin when more values than palette entries.
- **as\_continuous** (*Optional[bool]*) – Interpret column values as continuous. Ex: Uses palette for an interpolation gradient when more values than palette entries.
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to color-like strings. Ex: {“car”: “red”, “truck”: “#000”}

- **default\_mapping** (*Optional[str]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping="gray".
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.

**Returns** Plotter

**Return type** *Plotter*

**Example: Set a palette-valued column for the color, same as bind(point\_color='my\_column')**

```
g2a = g.encode_point_color('my_int32_palette_column')
g2b = g.encode_point_color('my_int64_rgb_column')
```

**Example: Set a cold-to-hot gradient of along the spectrum blue, yellow, red**

```
g2 = g.encode_point_color('my_numeric_col', palette=["blue", "yellow",
↪ "red"], as_continuous=True)
```

**Example: Round-robin sample from 5 colors in hex format**

```
g2 = g.encode_point_color('my_distinctly_valued_col', palette=["#000", "
↪ #00F", "#0F0", "#0FF", "#FFF"], as_categorical=True)
```

**Example: Map specific values to specific colors, including with a default**

```
g2a = g.encode_point_color('brands', categorical_mapping={'toyota': 'red',
↪ 'ford': 'blue'})
g2a = g.encode_point_color('brands', categorical_mapping={'toyota': 'red',
↪ 'ford': 'blue'}, default_mapping='gray')
```

**static encode\_point\_icon**(*column*, *categorical\_mapping=None*, *continuous\_binning=None*,  
*default\_mapping=None*, *comparator=None*, *for\_default=True*,  
*for\_current=False*, *as\_text=False*, *blend\_mode=None*, *style=None*,  
*border=None*, *shape=None*)

Set node icon with more control than bind(). Values from Font Awesome 4 such as “laptop”: <https://fontawesome.com/v4.7.0/icons/>

#### Parameters

- **column** (*str*) – Data column name
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to icon name strings. Ex: {"toyota": "car", "ford": "truck"}
- **default\_mapping** (*Optional[Union[int, float]]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping=50.
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.
- **as\_text** (*Optional[bool]*) – Values should instead be treated as raw strings, instead of icons and images. (Default False.)

- **blend\_mode** (*Optional[str]*) – CSS blend mode
- **style** (*Optional[dict]*) – CSS filter properties - opacity, saturation, luminosity, grayscale, and more
- **border** (*Optional[dict]*) – Border properties - ‘width’, ‘color’, and ‘stroke’

Returns Plotter

Return type *Plotter*

**Example:** Set a string column of icons for the point icons, same as `bind(point_icon='my_column')`

```
g2a = g.encode_point_icon('my_icons_column')
```

**Example:** Map specific values to specific icons, including with a default

```
g2a = g.encode_point_icon('brands', categorical_mapping={'toyota': 'car',
↳ 'ford': 'truck'})
g2b = g.encode_point_icon('brands', categorical_mapping={'toyota': 'car',
↳ 'ford': 'truck'}, default_mapping='question')
```

**Example:** Map countries to abbreviations

```
g2b = g.encode_point_icon('country_abbrev', as_text=True)
g2b = g.encode_point_icon('country', as_text=True, categorical_mapping={
↳ 'England': 'UK', 'America': 'US'}, default_mapping='')
```

**Example:** Border

```
g2b = g.encode_point_icon('country', border={'width': 3, color: 'black',
↳ 'stroke': 'dashed'}, 'categorical_mapping={'England': 'UK', 'America':
↳ 'US'})
```

**static encode\_point\_size** (*column*, *categorical\_mapping=None*, *default\_mapping=None*,  
*for\_default=True, for\_current=False*)

Set point size with more control than `bind()`

**Parameters**

- **column** (*str*) – Data column name
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to numbers. Ex: {“car”: 100, “truck”: 200}
- **default\_mapping** (*Optional[Union[int, float]]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping=50.
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.

Returns Plotter

Return type *Plotter*

**Example:** Set a numerically-valued column for the size, same as `bind(point_size='my_column')`

```
g2a = g.encode_point_size('my_numeric_column')
```

**Example: Map specific values to specific colors, including with a default**

```
g2a = g.encode_point_size('brands', categorical_mapping={'toyota': 100,
↳ 'ford': 200})
g2b = g.encode_point_size('brands', categorical_mapping={'toyota': 100,
↳ 'ford': 200}, default_mapping=50)
```

```
static from_cugraph(G, node_attributes=None, edge_attributes=None, load_nodes=True,
load_edges=True, merge_if_existing=True)
```

**Parameters**

- **node\_attributes** (Optional[List[str]]) –
- **edge\_attributes** (Optional[List[str]]) –
- **load\_nodes** (bool) –
- **load\_edges** (bool) –
- **merge\_if\_existing** (bool) –

```
static from_igraph(ig, node_attributes=None, edge_attributes=None, load_nodes=True,
load_edges=True)
```

**Parameters**

- **node\_attributes** (Optional[List[str]]) –
- **edge\_attributes** (Optional[List[str]]) –

```
static graph(ig)
```

```
static gremlin(queries)
```

Run one or more gremlin queries and get back the result as a graph object To support cosmosdb, sends as strings

**Example: Login and plot**

```
import graphistry
(graphistry
 .gremlin_client(my_gremlin_client)
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Parameters** **queries** (Union[str, Iterable[str]]) –

**Return type** Plottable

```
static gremlin_client(gremlin_client=None)
```

Pass in a generic gremlin python client

**Example: Login and plot**

```
import graphistry
from gremlin_python.driver.client import Client

my_gremlin_client = Client(
```

(continues on next page)



(continued from previous page)

```
f'wss://MY_ACCOUNT.gremlin.cosmosdb.azure.com:443/',
'g',
username=f"/dbs/MY_DB/colls/{self.COSMOS_CONTAINER}",
password=self.COSMOS_PRIMARY_KEY,
message_serializer=GraphSONSerializersV2d0())

(graphistry
 .gremlin_client(my_gremlin_client)
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Parameters** `gremlin_client` (Optional[Any]) –**Return type** `Plotter`**static** `gsql` (*query*, *bindings=None*, *dry\_run=False*)

Run Tigergraph query in interpreted mode and return transformed Plottable

**param** `query` Code to run**type** `query` str**param** `bindings` Mapping defining names of returned ‘edges’ and/or ‘nodes’, defaults to @@nodeList and @@edgeList**type** `bindings` Optional[dict]**param** `dry_run` Return target URL without running**type** `dry_run` bool**returns** Plotter**rtype** Plotter**Example: Minimal**

```
import graphistry
tg = graphistry.tigergraph()
tg.gsql("""
INTERPRET QUERY () FOR GRAPH Storage {

    OrAccum<BOOL> @@stop;
    ListAccum<EDGE> @@edgeList;
    SetAccum<vertex> @@set;

    @@set += to_vertex("61921", "Pool");

    Start = @@set;

    while Start.size() > 0 and @@stop == false do

        Start = select t from Start:s-(:e)-:t
        where e.goUpper == TRUE
        accum @@edgeList += e
        having t.type != "Service";
    end;
```

(continues on next page)

(continued from previous page)

```

    print @@edgeList;
}
""").plot()
```

**Example: Full**

```

import graphistry
tg = graphistry.tigergraph()
tg.gsql("""
INTERPRET QUERY () FOR GRAPH Storage {

    OrAccum<BOOL> @@stop;
    ListAccum<EDGE> @@edgeList;
    SetAccum<vertex> @@set;

    @@set += to_vertex("61921", "Pool");

    Start = @@set;

    while Start.size() > 0 and @@stop == false do

        Start = select t from Start:s-(:e)-:t
        where e.goUpper == TRUE
        accum @@edgeList += e
        having t.type != "Service";
    end;

    print @@my_edge_list;
}
""", {'edges': 'my_edge_list'}).plot()
```

**static gsql\_endpoint** (*self*, *method\_name*, *args*={}, *bindings*=None, *db*=None, *dry\_run*=False)

Invoke Tigergraph stored procedure at a user-defined endpoint and return transformed Plottable

**Parameters**

- **method\_name** (*str*) – Stored procedure name
- **args** (*Optional[dict]*) – Named endpoint arguments
- **bindings** (*Optional[dict]*) – Mapping defining names of returned ‘edges’ and/or ‘nodes’, defaults to @@nodeList and @@edgeList
- **db** (*Optional[str]*) – Name of the database, defaults to value set in .tigergraph(...)
- **dry\_run** (*bool*) – Return target URL without running

**Returns** Plotter

**Return type** *Plotter*

**Example: Minimal**

```

import graphistry
tg = graphistry.tigergraph(db='my_db')
tg.gsql_endpoint('neighbors').plot()
```

**Example: Full**

```
import graphistry
tg = graphistry.tigergraph()
tg.gsql_endpoint('neighbors', {'k': 2}, {'edges': 'my_edge_list'}, 'my_db
↪').plot()
```

**Example: Read data**

```
import graphistry
tg = graphistry.tigergraph()
out = tg.gsql_endpoint('neighbors')
(nodes_df, edges_df) = (out._nodes, out._edges)
```

```
static hypergraph (raw_events,          entity_types=None,          opts={},          drop_na=True,
                   drop_edge_attrs=False, verbose=True, direct=False, engine='pandas',
                   npartitions=None, chunksize=None)
```

Transform a dataframe into a hypergraph.

**Parameters**

- **raw\_events** (*pandas.DataFrame*) – Dataframe to transform (pandas or cudf).
- **entity\_types** (*Optional[list]*) – Columns (strings) to turn into nodes, None signifies all
- **opts** (*dict*) – See below
- **drop\_edge\_attrs** (*bool*) – Whether to include each row’s attributes on its edges, defaults to False (include)
- **verbose** (*bool*) – Whether to print size information
- **direct** (*bool*) – Omit hypernode and instead strongly connect nodes in an event
- **engine** (*bool*) – String (pandas, cudf, ...) for engine to use
- **npartitions** (*Optional[int]*) – For distributed engines, how many coarse-grained pieces to split events into
- **chunksize** (*Optional[int]*) – For distributed engines, split events after chunksize rows

Create a graph out of the dataframe, and return the graph components as dataframes, and the renderable result Plotter. Hypergraphs reveal relationships between rows and between column values. This transform is useful for lists of events, samples, relationships, and other structured high-dimensional data.

Specify local compute engine by passing *engine*='pandas', 'cudf', 'dask', 'dask\_cudf' (default: 'pandas'). If events are not in that engine’s format, they will be converted into it.

The transform creates a node for every unique value in the *entity\_types* columns (default: all columns). If *direct*=False (default), every row is also turned into a node. Edges are added to connect every table cell to its originating row’s node, or if *direct*=True, to the other nodes from the same row. Nodes are given the attribute 'type' corresponding to the originating column name, or in the case of a row, 'EventID'. Options further control the transform, such column category definitions for controlling whether values reoccurring in different columns should be treated as one node, or whether to only draw edges between certain column type pairs.

Consider a list of events. Each row represents a distinct event, and each column some metadata about an event. If multiple events have common metadata, they will be transitively connected through those metadata values. The layout algorithm will try to cluster the events together. Conversely, if an event has unique metadata, the unique metadata will turn into nodes that only have connections to the event node, and the clustering algorithm will cause them to form a ring around the event node.

Best practice is to set `EVENTID` to a row's unique ID, `SKIP` to all non-categorical columns (or `entity_types` to all categorical columns), and `CATEGORY` to group columns with the same kinds of values.

To prevent creating nodes for null values, set `drop_na=True`. Some dataframe engines may have undesirable null handling, and recommend replacing `None` values with `np.nan`.

The optional `opts={...}` configuration options are:

- `'EVENTID'`: Column name to inspect for a row ID. By default, uses the row index.
- `'CATEGORIES'`: Dictionary mapping a category name to inhabiting columns. E.g., `{ 'IP': ['srcAddress', 'dstAddress'] }`. If the same IP appears in both columns, this makes the transform generate one node for it, instead of one for each column.
- `'DELIM'`: When creating node IDs, defines the separator used between the column name and node value
- `'SKIP'`: List of column names to not turn into nodes. For example, dates and numbers are often skipped.
- `'EDGES'`: For `direct=True`, instead of making all edges, pick column pairs. E.g., `{ 'a': ['b', 'd'], 'd': ['d'] }` creates edges between columns `a->b` and `a->d`, and self-edges `d->d`.

**Returns** `{ 'entities': DF, 'events': DF, 'edges': DF, 'nodes': DF, 'graph': Plotter }`

**Return type** dict

#### Example: Connect user<-row->boss

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df)
g = h['graph'].plot()
```

#### Example: Connect user->boss

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

#### Example: Connect user<->boss

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True, opts={'EDGES': {'user': ['boss'], 'boss': ['user']}})
g = h['graph'].plot()
```

#### Example: Only consider some columns for nodes

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, entity_types=['boss'])
g = h['graph'].plot()
```

#### Example: Collapse matching user::<id> and boss::<id> nodes into one person::<id> node

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, opts={'CATEGORIES': {'person': ['user', 'boss']}})
g = h['graph'].plot()
```

#### Example: Use cudf engine instead of pandas

```
import cudf, graphistry
users_gdf = cudf.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_gdf, engine='cudf')
g = h['graph'].plot()
```

#### Parameters

- **entity\_types** (Optional[List[str]]) –
- **opts** (dict) –
- **drop\_na** (bool) –
- **drop\_edge\_attrs** (bool) –
- **verbose** (bool) –
- **direct** (bool) –
- **engine** (str) –
- **npartitions** (Optional[int]) –
- **chunksize** (Optional[int]) –

**static idp\_name** (value=None)

Set or get the idp\_name when register/login.

**static infer\_labels** (self)

**Returns** Plotter w/neo4j

- Prefers point\_title/point\_label if available
- Fallback to node id
- Raises exception if no nodes available, no likely candidates, and no matching node id fallback

#### Example

```
import graphistry
g = graphistry.nodes(pd.read_csv('nodes.csv'), 'id_col').infer_labels()
g.plot()
```

**static layout\_settings** (play=None, locked\_x=None, locked\_y=None, locked\_r=None, left=None, top=None, right=None, bottom=None, lin\_log=None, strong\_gravity=None, dissuade\_hubs=None, edge\_influence=None, precision\_vs\_speed=None, gravity=None, scaling\_ratio=None)

Set layout options. Additive over previous settings.

Corresponds to options at <https://hub.graphistry.com/docs/api/1/rest/url/#urloptions>

**Example: Animated radial layout**

```
import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'boss': ['c', 'c', 'e', 'e
→']})
nodes = pd.DataFrame({
    'n': ['a', 'b', 'c', 'd', 'e'],
    'y': [1, 1, 2, 3, 4],
    'x': [1, 1, 0, 0, 0],
})
g = (graphistry
    .edges(edges, 's', 'd')
    .nodes(nodes, 'n')
    .layout_settings(locked_r=True, play=2000)
g.plot())
```

**Parameters**

- **play** (Optional[int]) –
- **locked\_x** (Optional[bool]) –
- **locked\_y** (Optional[bool]) –
- **locked\_r** (Optional[bool]) –
- **left** (Optional[float]) –
- **top** (Optional[float]) –
- **right** (Optional[float]) –
- **bottom** (Optional[float]) –
- **lin\_log** (Optional[bool]) –
- **strong\_gravity** (Optional[bool]) –
- **dissuade\_hubs** (Optional[bool]) –
- **edge\_influence** (Optional[float]) –
- **precision\_vs\_speed** (Optional[float]) –
- **gravity** (Optional[float]) –
- **scaling\_ratio** (Optional[float]) –

**static login** (*username, password, org\_name=None, fail\_silent=False*)

Authenticate and set token for reuse (api=3). If token\_refresh\_ms (default: 10min), auto-refreshes token.  
By default, must be reinvoked within 24hr.

**static name** (*name*)

Upload name

**Parameters name** (*str*) – Upload name

**static neptune** (*NEPTUNE\_READER\_HOST=None, NEPTUNE\_READER\_PORT=None, NEPTUNE\_READER\_PROTOCOL='wss', endpoint=None, gremlin\_client=None*)

Provide credentials as arguments, as environment variables, or by providing a gremlinpython client Environment variable names are the same as the constructor argument names If endpoint provided, do not need host/port/protocol If no client provided, create (connect)

**Example: Login and plot via parrams**

```
import graphistry
(graphistry
 .neptune(
     NEPTUNE_READER_PROTOCOL='wss'
     NEPTUNE_READER_HOST='neptunedbcluster-xyz.cluster-ro-abc.us-
↪east-1.neptune.amazonaws.com'
     NEPTUNE_READER_PORT='8182'
 )
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Example: Login and plot via env vars**

```
import graphistry
(graphistry
 .neptune()
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Example: Login and plot via endpoint**

```
import graphistry
(graphistry
 .neptune(endpoint='wss://neptunedbcluster-xyz.cluster-ro-abc.us-
↪east-1.neptune.amazonaws.com:8182/gremlin')
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Example: Login and plot via client**

```
import graphistry
(graphistry
 .neptune(gremlin_client=client)
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Parameters**

- **NEPTUNE\_READER\_HOST** (Optional[str]) –
- **NEPTUNE\_READER\_PORT** (Optional[str]) –
- **NEPTUNE\_READER\_PROTOCOL** (Optional[str]) –
- **endpoint** (Optional[str]) –
- **gremlin\_client** (Optional[Any]) –

**Return type** *Plotter*

**static nodes** (*nodes*, *node=None*, *\*args*, *\*\*kwargs*)

Specify the set of nodes and associated data. If a callable, will be called with current Plotter and whatever positional+named arguments

Must include any nodes referenced in the edge list.

**Parameters** `nodes` (*Pandas dataframe or Callable*) – Nodes and their attributes.

**Returns** Plotter

**Return type** *Plotter*

### Example

```
import graphistry

es = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
g = graphistry
    .bind(source='src', destination='dst')
    .edges(es)

vs = pandas.DataFrame({'v': [0,1,2], 'lbl': ['a', 'b', 'c']})
g = g.bind(node='v').nodes(vs)

g.plot()
```

### Example

```
import graphistry

es = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
g = graphistry.edges(es, 'src', 'dst')

vs = pandas.DataFrame({'v': [0,1,2], 'lbl': ['a', 'b', 'c']})
g = g.nodes(vs, 'v')

g.plot()
```

### Example

```
:: import graphistry

def sample_nodes(g, n): return g._nodes.sample(n)

df = pandas.DataFrame({'id': [0,1,2], 'v': [1,2,0]})

graphistry .nodes(df, 'id') ..nodes(sample_nodes, n=2) ..nodes(sample_nodes, None, 2) # equivalent
.plot()
```

**static** `nodexl(xls_or_url, source='default', engine=None, verbose=False)`

#### Parameters

- **xls\_or\_url** – file/http path string to a nodexl-generated xls, or a pandas ExcelFile() object
- **source** – optionally activate binding by string name for a known nodexl data source ('twitter', 'wikimedia')
- **engine** – optionally set a pandas Excel engine
- **verbose** – optionally enable printing progress by overriding to True

**static** `not_implemented_thunk()`

**static** `org_name(value=None)`

Set or get the org\_name when register/login.



**static personal\_key\_id** (*value=None*)

Set or get the personal\_key\_id when register.

**Parameters** *value* (Optional[str]) –

**static personal\_key\_secret** (*value=None*)

Set or get the personal\_key\_secret when register.

**Parameters** *value* (Optional[str]) –

**static pipe** (*graph\_transform, \*args, \*\*kwargs*)

Create new Plotter derived from current

**Parameters** *graph\_transform* (Callable) –

### Example: Simple

```
import graphistry

def fill_missing_bindings(g, source='src', destination='dst'):
    return g.bind(source=source, destination=destination)

graphistry
    .edges(pandas.DataFrame({'src': [0,1,2], 'd': [1,2,0]}))
    .pipe(fill_missing_bindings, destination='d') # binds 'src'
    .plot()
```

**Return type** Plottable

**static pkey\_login** (*personal\_key\_id, personal\_key\_secret, org\_name=None, fail\_silent=False*)

Authenticate with personal key/secret and set token for reuse (api=3). If token\_refresh\_ms (default: 10min), auto-refreshes token. By default, must be reinvoked within 24hr.

**static privacy** (*mode=None, notify=None, invited\_users=None, mode\_action=None, message=None*)

Set global default sharing mode

#### Parameters

- **mode** (*str*) – Either “private” or “public” or “organization”
- **notify** (*bool*) – Whether to email the recipient(s) upon upload
- **invited\_users** (*List*) – List of recipients, where each is {“email”: str, “action”: str} and action is “10” (view) or “20” (edit)
- **mode\_action** (*str*) – Only used when mode=“organization”, action for sharing within organization, “10” (view) or “20” (edit), default is “20”

Requires an account with sharing capabilities.

Shared datasets will appear in recipients’ galleries.

If mode is set to “private”, only accounts in invited\_users list can access. Mode “public” permits viewing by any user with the URL.

Action “10” (view) gives read access, while action “20” (edit) gives edit access, like changing the sharing mode.

When notify is true, uploads will trigger notification emails to invitees. Email will use visualization’s “.name()”

### Example: Limit visualizations to current user

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
graphistry.privacy() # default uploads to mode="private"

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

**Example: Default to publicly viewable visualizations**

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
graphistry.privacy(mode="public") # can skip calling .privacy() for_
↳this default

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

**Example: Default to sharing with select teammates, and keep notifications opt-in**

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
graphistry.privacy(
    mode="private",
    invited_users=[
        {"email": "friend1@acme.org", "action": "10"}, # view
        {"email": "friend2@acme.org", "action": "20"}, # edit
    ],
    notify=False)

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

**Example: Keep visualizations public and email notifications upon upload**

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
graphistry.privacy(
    mode="public",
    invited_users=[
        {"email": "friend1@acme.org", "action": "10"}, # view
        {"email": "friend2@acme.org", "action": "20"}, # edit
    ],
    notify=True)

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
```

(continues on next page)

(continued from previous page)

```
g = h['graph']
g = g.name('my cool viz') # For friendlier invitations
g.plot()
```

**Parameters** `message` (Optional[str]) –

**static protocol** (*value=None*)

Set or get the protocol ('http' or 'https'). Set automatically when using a server alias. Also set via environment variable GRAPHISTRY\_PROTOCOL.

**static refresh** (*token=None, fail\_silent=False*)

Use self or provided JWT token to get a fresher one. If self token, internalize upon refresh.

**static register** (*key=None, username=None, password=None, token=None, personal\_key\_id=None, personal\_key\_secret=None, server=None, protocol=None, api=None, certificate\_validation=None, bolt=None, token\_refresh\_ms=600000, store\_token\_creds\_in\_memory=None, client\_protocol\_hostname=None, org\_name=None, idp\_name=None, is\_sso\_login=False, sso\_timeout=50*)

API key registration and server selection

Changing the key effects all derived Plotter instances.

Provide one of key (deprecated `api=1`), username/password (`api=3`) or temporary token (`api=3`).

#### Parameters

- **key** (Optional[str]) – API key (deprecated 1.0 API)
- **username** (Optional[str]) – Account username (2.0 API).
- **password** (Optional[str]) – Account password (2.0 API).
- **token** (Optional[str]) – Valid Account JWT token (2.0). Provide token, or username/password, but not both.
- **personal\_key\_id** (Optional[str]) – Personal Key id for service account.
- **personal\_key\_secret** (Optional[str]) – Personal Key secret for service account.
- **server** (Optional[str]) – URL of the visualization server.
- **protocol** (Optional[str]) – Protocol to use for server uploaders, defaults to “https”.
- **api** (Optional[Literal[1, 3]]) – API version to use, defaults to 1 (deprecated slow json 1.0 API), prefer 3 (2.0 API with Arrow+JWT)
- **certificate\_validation** (Optional[bool]) – Override default-on check for valid TLS certificate by setting to True.
- **bolt** (Union[dict, Any]) – Neo4j bolt information. Optional driver or named constructor arguments for instantiating a new one.
- **protocol** – Protocol used to contact visualization server, defaults to “https”.
- **token\_refresh\_ms** (int) – Ignored for now; JWT token auto-refreshed on plot() calls.
- **store\_token\_creds\_in\_memory** (Optional[bool]) – Store username/password in-memory for JWT token refreshes (Token-originated have a hard limit, so always-on requires creds somewhere)

- **client\_protocol\_hostname** (*Optional[str]*) – Override protocol and host shown in browser. Defaults to protocol/server or envvar GRAPHISTRY\_CLIENT\_PROTOCOL\_HOSTNAME.
- **org\_name** (*Optional[str]*) – Set login organization's name(slug). Defaults to user's personal organization.
- **idp\_name** (*Optional[str]*) – Set sso login idp name. Default as None (for site-wide SSO / for the only idp record).
- **sso\_timeout** (*Optional[int]*) – Set sso login getting token timeout in seconds (blocking mode), set to None if non-blocking mode. Default as SSO\_GET\_TOKEN\_ELAPSE\_SECONDS.

Returns None.

Return type None

**Example: Standard (2.0 api by org\_name via SSO configured for site or for organization with only 1 IdP)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', org_name=
↳ "org-name", idp_name="idp-name")
```

**Example: Standard (2.0 api by org\_name via SSO IdP configured for an organization)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', org_name=
↳ "org-name")
```

**Example: Standard (2.0 api by username/password with org\_name)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', username=
↳ 'person', password='pwd', org_name="org-name")
```

**Example: Standard (2.0 api by username/password) without org\_name**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', username=
↳ 'person', password='pwd')
```

**Example: Standard (2.0 api by token)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', token='abc
↳')
```

**Example: Standard (by personal\_key\_id/personal\_key\_secret)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', personal_
↳ key_id='ZD5872XKNF', personal_key_secret='SA0JJ2DTVT6LLO2S')
```

**Example: Remote browser to Graphistry-provided notebook server (2.0)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='nginx', client_
↳ protocol_hostname='https://my.site.com', token='abc')
```

(continues on next page)

(continued from previous page)

**Example: Standard (1.0)**

```
import graphistry
graphistry.register(api=1, key="my api key")
```

Parameters **is\_sso\_login** (Optional[bool]) –

**relogin** ()

**static scene\_settings** (*menu=None, info=None, show\_arrows=None, point\_size=None, edge\_curvature=None, edge\_opacity=None, point\_opacity=None*)

**Parameters**

- **menu** (Optional[bool]) –
- **info** (Optional[bool]) –
- **show\_arrows** (Optional[bool]) –
- **point\_size** (Optional[float]) –
- **edge\_curvature** (Optional[float]) –
- **edge\_opacity** (Optional[float]) –
- **point\_opacity** (Optional[float]) –

**static server** (*value=None*)

Get the hostname of the server or set the server using hostname or aliases. Also set via environment variable GRAPHISTRY\_HOSTNAME.

**static set\_bolt\_driver** (*driver=None*)

**static settings** (*height=None, url\_params={}, render=None*)

**static sso\_get\_token** ()

Get authentication token in SSO non-blocking mode

**static sso\_login** (*org\_name=None, idp\_name=None, sso\_timeout=50*)

Authenticate with SSO and set token for reuse (api=3).

**Parameters**

- **org\_name** (Optional[str]) – Set login organization's name(slug). Defaults to user's personal organization.
- **idp\_name** (Optional[str]) – Set sso login idp name. Default as None (for site-wide SSO / for the only idp record).
- **sso\_timeout** (Optional[int]) – Set sso login getting token timeout in seconds (blocking mode), set to None if non-blocking mode. Default as SSO\_GET\_TOKEN\_ELAPSE\_SECONDS.

**Returns** None.

**Return type** None

SSO Login logic.

**static sso\_state** (*value=None*)

Set or get the sso\_state when register/sso login.

**static store\_token\_creds\_in\_memory** (*value=None*)

Cache credentials for JWT token access. Default off due to not being safe.

**static style** (*bg=None, fg=None, logo=None, page=None*)

Creates a base plotter with some style settings.

For parameters, see `plotter.style`.

**Returns** Plotter

**Return type** *Plotter*

**Example**

```
import graphistry
graphistry.style(bg={'color': 'black'})
```

**static switch\_org** (*value*)

**static tigergraph** (*protocol='http', server='localhost', web\_port=14240, api\_port=9000, db=None, user='tigergraph', pwd='tigergraph', verbose=False*)

Register Tigergraph connection setting defaults

**Parameters**

- **protocol** (*Optional[str]*) – Protocol used to contact the database.
- **server** (*Optional[str]*) – Domain of the database
- **web\_port** (*Optional[int]*) –
- **api\_port** (*Optional[int]*) –
- **db** (*Optional[str]*) – Name of the database
- **user** (*Optional[str]*) –
- **pwd** (*Optional[str]*) –
- **verbose** (*Optional[bool]*) – Whether to print operations

**Returns** Plotter

**Return type** *Plotter*

**Example: Standard**

```
import graphistry
tg = graphistry.tigergraph(protocol='https', server='acme.com', db='my_db', user='alice', pwd='tigergraph2')
```

**static verify\_token** (*token=None, fail\_silent=False*)

Return True iff current or provided token is still valid

**Return type** `bool`

`graphistry.pygraphistry.addStyle` (*bg=None, fg=None, logo=None, page=None*)

Creates a base plotter with some style settings.

For parameters, see `plotter.addStyle`.

**Returns** Plotter

**Return type** *Plotter*

**Example**

```
import graphistry
graphistry.addStyle(bg={'color': 'black'})
```

`graphistry.pygraphistry.api_token` (*value=None*)

Set or get the API token. Also set via environment variable GRAPHISTRY\_API\_TOKEN.

`graphistry.pygraphistry.bind` (*node=None, source=None, destination=None, edge\_title=None, edge\_label=None, edge\_color=None, edge\_weight=None, edge\_icon=None, edge\_size=None, edge\_opacity=None, edge\_source\_color=None, edge\_destination\_color=None, point\_title=None, point\_label=None, point\_color=None, point\_weight=None, point\_icon=None, point\_size=None, point\_opacity=None, point\_x=None, point\_y=None*)

Create a base plotter.

Typically called at start of a program. For parameters, see `plotter.bind()`.

**Returns** Plotter

**Return type** *Plotter*

#### Example

```
import graphistry
g = graphistry.bind()
```

`graphistry.pygraphistry.bolt` (*driver=None*)

**Parameters** **driver** – Neo4j Driver or arguments for `GraphDatabase.driver({...})`

**Returns** Plotter w/neo4j

Call this to create a Plotter with an overridden neo4j driver.

#### Example

```
import graphistry
g = graphistry.bolt({ server: 'bolt://...', auth: ('<username>', '
↳<password>') })
```

```
import neo4j
import graphistry

driver = neo4j.GraphDatabase.driver(...)

g = graphistry.bolt(driver)
```

`graphistry.pygraphistry.client_protocol_hostname` (*value=None*)

Get/set the client protocol+hostname for when display urls (distinct from uploading). Also set via environment variable GRAPHISTRY\_CLIENT\_PROTOCOL\_HOSTNAME. Defaults to hostname and no protocol (reusing environment protocol)

`graphistry.pygraphistry.cosmos` (*COSMOS\_ACCOUNT=None, COSMOS\_DB=None, COSMOS\_CONTAINER=None, COSMOS\_PRIMARY\_KEY=None, gremlin\_client=None*)

Provide credentials as arguments, as environment variables, or by providing a gremlinpython client Environment variable names are the same as the constructor argument names If no client provided, create (connect)

**Parameters**

- **COSMOS\_ACCOUNT** (Optional[str]) – cosmos account

- **COSMOS\_DB** (Optional[str]) – cosmos db name
- **COSMOS\_CONTAINER** (Optional[str]) – cosmos container name
- **COSMOS\_PRIMARY\_KEY** (Optional[str]) – cosmos key
- **gremlin\_client** (Optional[Any]) – optional prebuilt client

**Return type** *Plotter*

**Returns** Plotter with data from a cypher query. This call binds *source*, *destination*, and *node*.

**Example: Login and plot**

```
import graphistry
(graphistry
 .cosmos (
     COSMOS_ACCOUNT='a',
     COSMOS_DB='b',
     COSMOS_CONTAINER='c',
     COSMOS_PRIMARY_KEY='d')
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

`graphistry.pygraphistry.cypher` (*query*, *params*={})

**Parameters**

- **query** – a cypher query
- **params** – cypher query arguments

**Returns** Plotter with data from a cypher query. This call binds *source*, *destination*, and *node*.

Call this to immediately execute a cypher query and store the graph in the resulting Plotter.

```
import graphistry
g = graphistry.bolt({ query='MATCH (a)-[r:PAYMENT]->(b) WHERE r.USD > 7000 AND r.USD < 10000 RETURN r ORDER BY r.USD DESC', params={
    "AccountId": 10 }})
```

`graphistry.pygraphistry.description` (*description*)

Upload description

**Parameters** **description** (*str*) – Upload description

`graphistry.pygraphistry.drop_graph` ()

Remove all graph nodes and edges from the database

**Return type** *Plotter*

`graphistry.pygraphistry.edges` (*edges*, *source*=None, *destination*=None, *\*args*, *\*\*kwargs*)

Specify edge list data and associated edge attribute values. If a callable, will be called with current Plotter and whatever positional+named arguments

**Parameters** **edges** (*Pandas dataframe, NetworkX graph, or IGraph graph*) – Edges and their attributes, or transform from Plotter to edges

**Returns** Plotter

**Return type** *Plotter*

**Example**



```
import graphistry
df = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
graphistry
    .bind(source='src', destination='dst')
    .edges(df)
    .plot()
```

**Example**

```
import graphistry
df = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
graphistry
    .edges(df, 'src', 'dst')
    .plot()
```

**Example**

```
:: import graphistry

def sample_edges(g, n): return g._edges.sample(n)

df = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})

graphistry .edges(df, 'src', 'dst') .edges(sample_edges, n=2) .edges(sample_edges, None, None, 2)
    # equivalent .plot()
```

```
graphistry.pygraphistry.encode_edge_badge(column, position='TopRight', categorical_mapping=None, continuous_binning=None, default_mapping=None, comparator=None, color=None, bg=None, fg=None, for_current=False, for_default=True, as_text=None, blend_mode=None, style=None, border=None, shape=None)
```

```
graphistry.pygraphistry.encode_edge_color(column, palette=None, as_categorical=None, as_continuous=None, categorical_mapping=None, default_mapping=None, for_default=True, for_current=False)
```

Set edge color with more control than bind()

**Parameters**

- **column** (*str*) – Data column name
- **palette** (*Optional[list]*) – Optional list of color-like strings. Ex: ["black", "#FF0", "rgb(255,255,255)"]. Used as a gradient for continuous and round-robin for categorical.
- **as\_categorical** (*Optional[bool]*) – Interpret column values as categorical. Ex: Uses palette via round-robin when more values than palette entries.
- **as\_continuous** (*Optional[bool]*) – Interpret column values as continuous. Ex: Uses palette for an interpolation gradient when more values than palette entries.
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to color-like strings. Ex: {"car": "red", "truck": "#000"}
- **default\_mapping** (*Optional[str]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping="gray".
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.

- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.

**Returns** Plotter

**Return type** *Plotter*

**Example:** See `encode_point_color`

```
graphistry.pygraphistry.encode_edge_icon(column, categorical_mapping=None, continuous_binning=None, default_mapping=None, comparator=None, for_default=True, for_current=False, as_text=False, blend_mode=None, style=None, border=None, shape=None)
```

Set edge icon with more control than `bind()`. Values from Font Awesome 4 such as “laptop”: <https://fontawesome.com/v4.7.0/icons/>

#### Parameters

- **column** (*str*) – Data column name
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to icon name strings. Ex: {“toyota”: ‘car’, “ford”: ‘truck’}
- **default\_mapping** (*Optional[Union[int, float]]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping=50.
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.
- **as\_text** (*Optional[bool]*) – Values should instead be treated as raw strings, instead of icons and images. (Default False.)
- **blend\_mode** (*Optional[str]*) – CSS blend mode
- **style** (*Optional[dict]*) – CSS filter properties - opacity, saturation, luminosity, grayscale, and more
- **border** (*Optional[dict]*) – Border properties - ‘width’, ‘color’, and ‘stroke’

**Returns** Plotter

**Return type** *Plotter*

**Example:** Set a string column of icons for the edge icons, same as `bind(edge_icon='my_column')`

```
g2a = g.encode_edge_icon('my_icons_column')
```

**Example:** Map specific values to specific icons, including with a default

```
g2a = g.encode_edge_icon('brands', categorical_mapping={'toyota': 'car', 'ford': 'truck'})
g2b = g.encode_edge_icon('brands', categorical_mapping={'toyota': 'car', 'ford': 'truck'}, default_mapping='question')
```

**Example:** Map countries to abbreviations

```
g2a = g.encode_edge_icon('country_abbrev', as_text=True)
g2b = g.encode_edge_icon('country', categorical_mapping={'England': 'UK',
↪ 'America': 'US'}, default_mapping='')
```

**Example: Border**

```
g2b = g.encode_edge_icon('country', border={'width': 3, color: 'black',
↪ 'stroke': 'dashed'}, 'categorical_mapping={'England': 'UK', 'America': 'US'}
↪)
```

```
graphistry.pygraphistry.encode_point_badge(column, position='TopRight', cat-
egorical_mapping=None, continu-
ous_binning=None, default_mapping=None,
comparator=None, color=None,
bg=None, fg=None, for_current=False,
for_default=True, as_text=None,
blend_mode=None, style=None, bor-
der=None, shape=None)

graphistry.pygraphistry.encode_point_color(column, palette=None, as_categorical=None,
as_continuous=None, categori-
cal_mapping=None, default_mapping=None,
for_default=True, for_current=False)
```

Set point color with more control than bind()

**Parameters**

- **column** (*str*) – Data column name
- **palette** (*Optional[list]*) – Optional list of color-like strings. Ex: ["black", "#FF0", "rgb(255,255,255)"]. Used as a gradient for continuous and round-robin for categorical.
- **as\_categorical** (*Optional[bool]*) – Interpret column values as categorical. Ex: Uses palette via round-robin when more values than palette entries.
- **as\_continuous** (*Optional[bool]*) – Interpret column values as continuous. Ex: Uses palette for an interpolation gradient when more values than palette entries.
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to color-like strings. Ex: {"car": "red", "truck": "#000"}
- **default\_mapping** (*Optional[str]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping="gray".
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.

**Returns** Plotter

**Return type** *Plotter*

**Example: Set a palette-valued column for the color, same as bind(point\_color='my\_column')**

```
g2a = g.encode_point_color('my_int32_palette_column')
g2b = g.encode_point_color('my_int64_rgb_column')
```

**Example: Set a cold-to-hot gradient of along the spectrum blue, yellow, red**

```
g2 = g.encode_point_color('my_numeric_col', palette=["blue", "yellow", "red"],
↳ as_continuous=True)
```

**Example: Round-robin sample from 5 colors in hex format**

```
g2 = g.encode_point_color('my_distinctly_valued_col', palette=["#000", "#00F",
↳ "#0F0", "#0FF", "#FFF"], as_categorical=True)
```

**Example: Map specific values to specific colors, including with a default**

```
g2a = g.encode_point_color('brands', categorical_mapping={'toyota': 'red',
↳ 'ford': 'blue'})
g2a = g.encode_point_color('brands', categorical_mapping={'toyota': 'red',
↳ 'ford': 'blue'}, default_mapping='gray')
```

`graphistry.pygraphistry.encode_point_icon(column, categorical_mapping=None, continuous_binning=None, default_mapping=None, comparator=None, for_default=True, for_current=False, as_text=False, blend_mode=None, style=None, border=None, shape=None)`

Set node icon with more control than `bind()`. Values from Font Awesome 4 such as “laptop”: <https://fontawesome.com/v4.7.0/icons/>

#### Parameters

- **column** (*str*) – Data column name
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to icon name strings. Ex: {“toyota”: ‘car’, “ford”: ‘truck’}
- **default\_mapping** (*Optional[Union[int, float]]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping=50.
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.
- **as\_text** (*Optional[bool]*) – Values should instead be treated as raw strings, instead of icons and images. (Default False.)
- **blend\_mode** (*Optional[str]*) – CSS blend mode
- **style** (*Optional[dict]*) – CSS filter properties - opacity, saturation, luminosity, grayscale, and more
- **border** (*Optional[dict]*) – Border properties - ‘width’, ‘color’, and ‘stroke’

**Returns** Plotter

**Return type** *Plotter*

**Example: Set a string column of icons for the point icons, same as `bind(point_icon='my_column')`**

```
g2a = g.encode_point_icon('my_icons_column')
```

**Example: Map specific values to specific icons, including with a default**

```
g2a = g.encode_point_icon('brands', categorical_mapping={'toyota': 'car',
↳ 'ford': 'truck'})
g2b = g.encode_point_icon('brands', categorical_mapping={'toyota': 'car',
↳ 'ford': 'truck'}, default_mapping='question')
```

**Example: Map countries to abbreviations**

```
g2b = g.encode_point_icon('country_abbrev', as_text=True)
g2b = g.encode_point_icon('country', as_text=True, categorical_mapping={
↳ 'England': 'UK', 'America': 'US'}, default_mapping='')
```

**Example: Border**

```
g2b = g.encode_point_icon('country', border={'width': 3, color: 'black',
↳ 'stroke': 'dashed'}, 'categorical_mapping={'England': 'UK', 'America': 'US'}
↳ )
```

```
graphistry.pygraphistry.encode_point_size(column, categorical_mapping=None, de-
                                          fault_mapping=None, for_default=True,
                                          for_current=False)
```

Set point size with more control than bind()

**Parameters**

- **column** (*str*) – Data column name
- **categorical\_mapping** (*Optional[dict]*) – Mapping from column values to numbers. Ex: {"car": 100, "truck": 200}
- **default\_mapping** (*Optional[Union[int, float]]*) – Augment categorical\_mapping with mapping for values not in categorical\_mapping. Ex: default\_mapping=50.
- **for\_default** (*Optional[bool]*) – Use encoding for when no user override is set. Default on.
- **for\_current** (*Optional[bool]*) – Use encoding as currently active. Clearing the active encoding resets it to default, which may be different. Default on.

**Returns** Plotter

**Return type** *Plotter*

**Example: Set a numerically-valued column for the size, same as bind(point\_size='my\_column')**

```
g2a = g.encode_point_size('my_numeric_column')
```

**Example: Map specific values to specific colors, including with a default**

```
g2a = g.encode_point_size('brands', categorical_mapping={'toyota': 100, 'ford'
↳ ': 200})
g2b = g.encode_point_size('brands', categorical_mapping={'toyota': 100, 'ford'
↳ ': 200}, default_mapping=50)
```

```
graphistry.pygraphistry.from_cugraph(G, node_attributes=None, edge_attributes=None,
                                     load_nodes=True, load_edges=True,
                                     merge_if_existing=True)
```

**Parameters**

- **node\_attributes** (Optional[List[str]]) –
- **edge\_attributes** (Optional[List[str]]) –
- **load\_nodes** (bool) –
- **load\_edges** (bool) –
- **merge\_if\_existing** (bool) –

graphistry.pygraphistry.**from\_igraph**(ig, node\_attributes=None, edge\_attributes=None, load\_nodes=True, load\_edges=True)

#### Parameters

- **node\_attributes** (Optional[List[str]]) –
- **edge\_attributes** (Optional[List[str]]) –

graphistry.pygraphistry.**graph**(ig)

graphistry.pygraphistry.**gremlin**(queries)

Run one or more gremlin queries and get back the result as a graph object To support cosmosdb, sends as strings

#### Example: Login and plot

```
import graphistry
(graphistry
 .gremlin_client(my_gremlin_client)
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Parameters** queries (Union[str, Iterable[str]]) –

**Return type** Plottable

graphistry.pygraphistry.**gremlin\_client**(gremlin\_client=None)

Pass in a generic gremlin python client

#### Example: Login and plot

```
import graphistry
from gremlin_python.driver.client import Client

my_gremlin_client = Client(
 f'wss://MY_ACCOUNT.gremlin.cosmosdb.azure.com:443/',
 'g',
 username=f"/dbs/MY_DB/colls/{self.COSMOS_CONTAINER}",
 password=self.COSMOS_PRIMARY_KEY,
 message_serializer=GraphSONSerializersV2d0())

(graphistry
 .gremlin_client(my_gremlin_client)
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Parameters** gremlin\_client (Optional[Any]) –

**Return type** *Plotter*

`graphistry.pygraphistry.gsql(query, bindings=None, dry_run=False)`

Run Tigergraph query in interpreted mode and return transformed Plottable

**param query** Code to run

**type query** str

**param bindings** Mapping defining names of returned 'edges' and/or 'nodes', defaults to @@nodeList and @@edgeList

**type bindings** Optional[dict]

**param dry\_run** Return target URL without running

**type dry\_run** bool

**returns** Plotter

**rtype** Plotter

### Example: Minimal

```
import graphistry
tg = graphistry.tigergraph()
tg.gsql("""
INTERPRET QUERY () FOR GRAPH Storage {

    OrAccum<BOOL> @@stop;
    ListAccum<EDGE> @@edgeList;
    SetAccum<vertex> @@set;

    @@set += to_vertex("61921", "Pool");

    Start = @@set;

    while Start.size() > 0 and @@stop == false do

        Start = select t from Start:s-(e)-:t
        where e.goUpper == TRUE
        accum @@edgeList += e
        having t.type != "Service";
    end;

    print @@edgeList;
}
""").plot()
```

### Example: Full

```
import graphistry
tg = graphistry.tigergraph()
tg.gsql("""
INTERPRET QUERY () FOR GRAPH Storage {

    OrAccum<BOOL> @@stop;
    ListAccum<EDGE> @@edgeList;
    SetAccum<vertex> @@set;

    @@set += to_vertex("61921", "Pool");
```

(continues on next page)

(continued from previous page)

```

Start = @@set;

while Start.size() > 0 and @@stop == false do

  Start = select t from Start:s-(:e)-:t
  where e.goUpper == TRUE
  accum @@edgeList += e
  having t.type != "Service";
end;

print @@my_edge_list;
}
""", {'edges': 'my_edge_list'}).plot()

```

`graphistry.pygraphistry.gsql_endpoint` (*self*, *method\_name*, *args*={}, *bindings*=None, *db*=None, *dry\_run*=False)

Invoke Tigergraph stored procedure at a user-defined endpoint and return transformed Plottable

#### Parameters

- **method\_name** (*str*) – Stored procedure name
- **args** (*Optional[dict]*) – Named endpoint arguments
- **bindings** (*Optional[dict]*) – Mapping defining names of returned ‘edges’ and/or ‘nodes’, defaults to @@nodeList and @@edgeList
- **db** (*Optional[str]*) – Name of the database, defaults to value set in `.tigergraph(...)`
- **dry\_run** (*bool*) – Return target URL without running

**Returns** Plotter

**Return type** *Plotter*

#### Example: Minimal

```

import graphistry
tg = graphistry.tigergraph(db='my_db')
tg.gsql_endpoint('neighbors').plot()

```

#### Example: Full

```

import graphistry
tg = graphistry.tigergraph()
tg.gsql_endpoint('neighbors', {'k': 2}, {'edges': 'my_edge_list', 'my_db'}).
  ↪ plot()

```

#### Example: Read data

```

import graphistry
tg = graphistry.tigergraph()
out = tg.gsql_endpoint('neighbors')
(nodes_df, edges_df) = (out._nodes, out._edges)

```

`graphistry.pygraphistry.hypergraph` (*raw\_events*, *entity\_types*=None, *opts*={}, *drop\_na*=True, *drop\_edge\_attrs*=False, *verbose*=True, *direct*=False, *engine*='pandas', *npartitions*=None, *chunksize*=None)

Transform a dataframe into a hypergraph.



## Parameters

- **raw\_events** (*pandas.DataFrame*) – Dataframe to transform (pandas or cudf).
- **entity\_types** (*Optional[list]*) – Columns (strings) to turn into nodes, None signifies all
- **opts** (*dict*) – See below
- **drop\_edge\_attrs** (*bool*) – Whether to include each row’s attributes on its edges, defaults to False (include)
- **verbose** (*bool*) – Whether to print size information
- **direct** (*bool*) – Omit hypernode and instead strongly connect nodes in an event
- **engine** (*bool*) – String (pandas, cudf, ...) for engine to use
- **npartitions** (*Optional[int]*) – For distributed engines, how many coarse-grained pieces to split events into
- **chunksize** (*Optional[int]*) – For distributed engines, split events after chunksize rows

Create a graph out of the dataframe, and return the graph components as dataframes, and the renderable result Plotter. Hypergraphs reveal relationships between rows and between column values. This transform is useful for lists of events, samples, relationships, and other structured high-dimensional data.

Specify local compute engine by passing *engine='pandas', 'cudf', 'dask', 'dask\_cudf'* (default: 'pandas'). If events are not in that engine’s format, they will be converted into it.

The transform creates a node for every unique value in the *entity\_types* columns (default: all columns). If *direct=False* (default), every row is also turned into a node. Edges are added to connect every table cell to its originating row’s node, or if *direct=True*, to the other nodes from the same row. Nodes are given the attribute 'type' corresponding to the originating column name, or in the case of a row, 'EventID'. Options further control the transform, such column category definitions for controlling whether values reoccurring in different columns should be treated as one node, or whether to only draw edges between certain column type pairs.

Consider a list of events. Each row represents a distinct event, and each column some metadata about an event. If multiple events have common metadata, they will be transitively connected through those metadata values. The layout algorithm will try to cluster the events together. Conversely, if an event has unique metadata, the unique metadata will turn into nodes that only have connections to the event node, and the clustering algorithm will cause them to form a ring around the event node.

Best practice is to set *EVENTID* to a row’s unique ID, *SKIP* to all non-categorical columns (or *entity\_types* to all categorical columns), and *CATEGORY* to group columns with the same kinds of values.

To prevent creating nodes for null values, set *drop\_na=True*. Some dataframe engines may have undesirable null handling, and recommend replacing None values with *np.nan*.

The optional *opts={...}* configuration options are:

- 'EVENTID': Column name to inspect for a row ID. By default, uses the row index.
- 'CATEGORIES': Dictionary mapping a category name to inhabiting columns. E.g., {'IP': ['srcAddress', 'dstAddress']}. If the same IP appears in both columns, this makes the transform generate one node for it, instead of one for each column.
- 'DELIM': When creating node IDs, defines the separator used between the column name and node value
- 'SKIP': List of column names to not turn into nodes. For example, dates and numbers are often skipped.
- 'EDGES': For *direct=True*, instead of making all edges, pick column pairs. E.g., {'a': ['b', 'd'], 'd': ['d']} creates edges between columns *a->b* and *a->d*, and self-edges *d->d*.

**Returns** {'entities': DF, 'events': DF, 'edges': DF, 'nodes': DF, 'graph': Plotter}

**Return type** dict

**Example: Connect user<-row->boss**

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df)
g = h['graph'].plot()
```

**Example: Connect user->boss**

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

**Example: Connect user<->boss**

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True, opts={'EDGES': {'user': [
↔ 'boss'], 'boss': ['user']}}})
g = h['graph'].plot()
```

**Example: Only consider some columns for nodes**

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, entity_types=['boss'])
g = h['graph'].plot()
```

**Example: Collapse matching user::<id> and boss::<id> nodes into one person::<id> node**

```
import graphistry
users_df = pd.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, opts={'CATEGORIES': {'person': ['user
↔ ', 'boss']}}})
g = h['graph'].plot()
```

**Example: Use cudf engine instead of pandas**

```
import cudf, graphistry
users_gdf = cudf.DataFrame({'user': ['a', 'b', 'x'], 'boss': ['x', 'x', 'y
↔ ']}))
h = graphistry.hypergraph(users_gdf, engine='cudf')
g = h['graph'].plot()
```

### Parameters

- **entity\_types** (Optional[List[str]]) –
- **opts** (dict) –
- **drop\_na** (bool) –
- **drop\_edge\_attrs** (bool) –
- **verbose** (bool) –

- **direct** (bool) –
- **engine** (str) –
- **npartitions** (Optional[int]) –
- **chunksize** (Optional[int]) –

graphistry.pygraphistry.**idp\_name** (value=None)  
Set or get the idp\_name when register/login.

graphistry.pygraphistry.**infer\_labels** (self)

**Returns** Plotter w/neo4j

- Prefers point\_title/point\_label if available
- Fallback to node id
- Raises exception if no nodes available, no likely candidates, and no matching node id fallback

### Example

```
import graphistry
g = graphistry.nodes(pd.read_csv('nodes.csv'), 'id_col').infer_labels()
g.plot()
```

graphistry.pygraphistry.**layout\_settings** (play=None, locked\_x=None, locked\_y=None, locked\_r=None, left=None, top=None, right=None, bottom=None, lin\_log=None, strong\_gravity=None, dissuade\_hubs=None, edge\_influence=None, precision\_vs\_speed=None, gravity=None, scaling\_ratio=None)

Set layout options. Additive over previous settings.

Corresponds to options at <https://hub.graphistry.com/docs/api/1/rest/url/#urloptions>

### Example: Animated radial layout

```
import graphistry, pandas as pd
edges = pd.DataFrame({'s': ['a', 'b', 'c', 'd'], 'boss': ['c', 'c', 'e', 'e']})
nodes = pd.DataFrame({
    'n': ['a', 'b', 'c', 'd', 'e'],
    'y': [1, 1, 2, 3, 4],
    'x': [1, 1, 0, 0, 0],
})
g = (graphistry
     .edges(edges, 's', 'd')
     .nodes(nodes, 'n')
     .layout_settings(locked_r=True, play=2000)
g.plot())
```

### Parameters

- **play** (Optional[int]) –
- **locked\_x** (Optional[bool]) –
- **locked\_y** (Optional[bool]) –
- **locked\_r** (Optional[bool]) –

- **left** (Optional[float]) –
- **top** (Optional[float]) –
- **right** (Optional[float]) –
- **bottom** (Optional[float]) –
- **lin\_log** (Optional[bool]) –
- **strong\_gravity** (Optional[bool]) –
- **dissuade\_hubs** (Optional[bool]) –
- **edge\_influence** (Optional[float]) –
- **precision\_vs\_speed** (Optional[float]) –
- **gravity** (Optional[float]) –
- **scaling\_ratio** (Optional[float]) –

`graphistry.pygraphistry.login(username, password, org_name=None, fail_silent=False)`

Authenticate and set token for reuse (api=3). If token\_refresh\_ms (default: 10min), auto-refreshes token. By default, must be reinvoked within 24hr.

`graphistry.pygraphistry.name(name)`

Upload name

**Parameters** `name` (*str*) – Upload name

`graphistry.pygraphistry.neptune(NEPTUNE_READER_HOST=None, NEPTUNE_READER_PORT=None, NEPTUNE_READER_PROTOCOL='wss', endpoint=None, gremlin_client=None)`

Provide credentials as arguments, as environment variables, or by providing a gremlinpython client  
Environment variable names are the same as the constructor argument names If endpoint provided, do not need host/port/protocol If no client provided, create (connect)

#### Example: Login and plot via parrams

```
import graphistry
(graphistry
 .neptune(
     NEPTUNE_READER_PROTOCOL='wss'
     NEPTUNE_READER_HOST='neptunedbcluster-xyz.cluster-ro-abc.us-east-1.neptune.amazonaws.com'
     NEPTUNE_READER_PORT='8182'
 )
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

#### Example: Login and plot via env vars

```
import graphistry
(graphistry
 .neptune()
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Example: Login and plot via endpoint**

```
import graphistry
(graphistry
 .neptune(endpoint='wss://neptunedbcluster-xyz.cluster-ro-abc.us-east-
↪1.neptune.amazonaws.com:8182/gremlin')
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Example: Login and plot via client**

```
import graphistry
(graphistry
 .neptune(gremlin_client=client)
 .gremlin('g.E().sample(10)')
 .fetch_nodes() # Fetch properties for nodes
 .plot())
```

**Parameters**

- **NEPTUNE\_READER\_HOST** (Optional[str]) –
- **NEPTUNE\_READER\_PORT** (Optional[str]) –
- **NEPTUNE\_READER\_PROTOCOL** (Optional[str]) –
- **endpoint** (Optional[str]) –
- **gremlin\_client** (Optional[Any]) –

**Return type** *Plotter*`graphistry.pygraphistry.nodes(nodes, node=None, *args, **kwargs)`

Specify the set of nodes and associated data. If a callable, will be called with current Plotter and whatever positional+named arguments

Must include any nodes referenced in the edge list.

**Parameters** **nodes** (*Pandas dataframe or Callable*) – Nodes and their attributes.

**Returns** Plotter

**Return type** *Plotter*

**Example**

```
import graphistry

es = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
g = graphistry
 .bind(source='src', destination='dst')
 .edges(es)

vs = pandas.DataFrame({'v': [0,1,2], 'lbl': ['a', 'b', 'c']})
g = g.bind(node='v').nodes(vs)

g.plot()
```

**Example**

```
import graphistry

es = pandas.DataFrame({'src': [0,1,2], 'dst': [1,2,0]})
g = graphistry.edges(es, 'src', 'dst')

vs = pandas.DataFrame({'v': [0,1,2], 'lbl': ['a', 'b', 'c']})
g = g.nodes(vs, 'v')

g.plot()
```

**Example**

```
:: import graphistry

def sample_nodes(g, n): return g._nodes.sample(n)

df = pandas.DataFrame({'id': [0,1,2], 'v': [1,2,0]})

graphistry .nodes(df, 'id') ..nodes(sample_nodes, n=2) ..nodes(sample_nodes, None, 2) # equivalent
.plot()
```

```
graphistry.pygraphistry.nodexl (xls_or_url, source='default', engine=None, verbose=False)
```

**Parameters**

- **xls\_or\_url** – file/http path string to a nodexl-generated xls, or a pandas ExcelFile() object
- **source** – optionally activate binding by string name for a known nodexl data source ('twitter', 'wikimedia')
- **engine** – optionally set a pandas Excel engine
- **verbose** – optionally enable printing progress by overriding to True

```
graphistry.pygraphistry.org_name (value=None)
```

Set or get the org\_name when register/login.

```
graphistry.pygraphistry.personal_key_id (value=None)
```

Set or get the personal\_key\_id when register.

**Parameters value** (Optional[str]) –

```
graphistry.pygraphistry.personal_key_secret (value=None)
```

Set or get the personal\_key\_secret when register.

**Parameters value** (Optional[str]) –

```
graphistry.pygraphistry.pipe (graph_transform, *args, **kwargs)
```

Create new Plotter derived from current

**Parameters graph\_transform** (Callable) –

**Example: Simple**

```
import graphistry

def fill_missing_bindings(g, source='src', destination='dst'):
    return g.bind(source=source, destination=destination)

graphistry
.edges(pandas.DataFrame({'src': [0,1,2], 'd': [1,2,0]}))
```

(continues on next page)

(continued from previous page)

```
.pipe(fill_missing_bindings, destination='d') # binds 'src'
.plot()
```

**Return type** Plottable

```
graphistry.pygraphistry.privacy(mode=None,          notify=None,          invited_users=None,
                                mode_action=None, message=None)
```

Set global default sharing mode

**Parameters**

- **mode** (*str*) – Either “private” or “public” or “organization”
- **notify** (*bool*) – Whether to email the recipient(s) upon upload
- **invited\_users** (*List*) – List of recipients, where each is {“email”: str, “action”: str} and action is “10” (view) or “20” (edit)
- **mode\_action** (*str*) – Only used when mode=“organization”, action for sharing within organization, “10” (view) or “20” (edit), default is “20”

Requires an account with sharing capabilities.

Shared datasets will appear in recipients’ galleries.

If mode is set to “private”, only accounts in invited\_users list can access. Mode “public” permits viewing by any user with the URL.

Action “10” (view) gives read access, while action “20” (edit) gives edit access, like changing the sharing mode.

When notify is true, uploads will trigger notification emails to invitees. Email will use visualization’s “.name()”

**Example: Limit visualizations to current user**

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
graphistry.privacy() # default uploads to mode="private"

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

**Example: Default to publicly viewable visualizations**

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
#graphistry.privacy(mode="public") # can skip calling .privacy() for_
↳this default

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()
```

**Example: Default to sharing with select teammates, and keep notifications opt-in**

```
import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
```

(continues on next page)

(continued from previous page)

```

graphistry.privacy(
    mode="private",
    invited_users=[
        {"email": "friend1@acme.org", "action": "10"}, # view
        {"email": "friend2@acme.org", "action": "20"}, # edit
    ],
    notify=False)

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph'].plot()

```

**Example: Keep visualizations public and email notifications upon upload**

```

import graphistry
graphistry.register(api=3, username='myuser', password='mypassword')
graphistry.privacy(
    mode="public",
    invited_users=[
        {"email": "friend1@acme.org", "action": "10"}, # view
        {"email": "friend2@acme.org", "action": "20"}, # edit
    ],
    notify=True)

#Subsequent uploads default to using .privacy() settings
users_df = pd.DataFrame({'user': ['a','b','x'], 'boss': ['x', 'x', 'y']})
h = graphistry.hypergraph(users_df, direct=True)
g = h['graph']
g = g.name('my cool viz') # For friendlier invitations
g.plot()

```

**Parameters message** (Optional[str]) –

`graphistry.pygraphistry.protocol` (value=None)

Set or get the protocol ('http' or 'https'). Set automatically when using a server alias. Also set via environment variable GRAPHISTRY\_PROTOCOL.

`graphistry.pygraphistry.refresh` (token=None, fail\_silent=False)

Use self or provided JWT token to get a fresher one. If self token, internalize upon refresh.

`graphistry.pygraphistry.register` (key=None, username=None, password=None, token=None, personal\_key\_id=None, personal\_key\_secret=None, server=None, protocol=None, api=None, certificate\_validation=None, bolt=None, token\_refresh\_ms=600000, store\_token\_creds\_in\_memory=None, client\_protocol\_hostname=None, org\_name=None, idp\_name=None, is\_sso\_login=False, sso\_timeout=50)

API key registration and server selection

Changing the key effects all derived Plotter instances.

Provide one of key (deprecated api=1), username/password (api=3) or temporary token (api=3).

**Parameters**

- **key** (Optional[str]) – API key (deprecated 1.0 API)



- **username** (*Optional[str]*) – Account username (2.0 API).
- **password** (*Optional[str]*) – Account password (2.0 API).
- **token** (*Optional[str]*) – Valid Account JWT token (2.0). Provide token, or username/password, but not both.
- **personal\_key\_id** (*Optional[str]*) – Personal Key id for service account.
- **personal\_key\_secret** (*Optional[str]*) – Personal Key secret for service account.
- **server** (*Optional[str]*) – URL of the visualization server.
- **protocol** (*Optional[str]*) – Protocol to use for server uploaders, defaults to “https”.
- **api** (*Optional[Literal[1, 3]]*) – API version to use, defaults to 1 (deprecated slow json 1.0 API), prefer 3 (2.0 API with Arrow+JWT)
- **certificate\_validation** (*Optional[bool]*) – Override default-on check for valid TLS certificate by setting to True.
- **bolt** (*Union[dict, Any]*) – Neo4j bolt information. Optional driver or named constructor arguments for instantiating a new one.
- **protocol** – Protocol used to contact visualization server, defaults to “https”.
- **token\_refresh\_ms** (*int*) – Ignored for now; JWT token auto-refreshed on plot() calls.
- **store\_token\_creds\_in\_memory** (*Optional[bool]*) – Store username/password in-memory for JWT token refreshes (Token-originated have a hard limit, so always-on requires creds somewhere)
- **client\_protocol\_hostname** (*Optional[str]*) – Override protocol and host shown in browser. Defaults to protocol/server or envvar GRAPHISTRY\_CLIENT\_PROTOCOL\_HOSTNAME.
- **org\_name** (*Optional[str]*) – Set login organization’s name(slug). Defaults to user’s personal organization.
- **idp\_name** (*Optional[str]*) – Set sso login idp name. Default as None (for site-wide SSO / for the only idp record).
- **sso\_timeout** (*Optional[int]*) – Set sso login getting token timeout in seconds (blocking mode), set to None if non-blocking mode. Default as SSO\_GET\_TOKEN\_ELAPSE\_SECONDS.

**Returns** None.

**Return type** None

**Example: Standard (2.0 api by org\_name via SSO configured for site or for organization with only 1 IdP)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', org_name="org-
↪name", idp_name="idp-name")
```

**Example: Standard (2.0 api by org\_name via SSO IdP configured for an organization)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', org_name="org-
↪name")
```

**Example: Standard (2.0 api by username/password with org\_name)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', username=
↳ 'person', password='pwd', org_name="org-name")
```

**Example: Standard (2.0 api by username/password) without org\_name**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', username=
↳ 'person', password='pwd')
```

**Example: Standard (2.0 api by token)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', token='abc')
```

**Example: Standard (by personal\_key\_id/personal\_key\_secret)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='200.1.1.1', personal_key_
↳ id='ZD5872XKNF', personal_key_secret='SA0JJ2DTVT6LLO2S')
```

**Example: Remote browser to Graphistry-provided notebook server (2.0)**

```
import graphistry
graphistry.register(api=3, protocol='http', server='nginx', client_protocol_
↳ hostname='https://my.site.com', token='abc')
```

**Example: Standard (1.0)**

```
import graphistry
graphistry.register(api=1, key="my api key")
```

**Parameters** `is_sso_login` (Optional[bool]) –

`graphistry.pygraphistry.scene_settings` (*menu=None, info=None, show\_arrows=None, point\_size=None, edge\_curvature=None, edge\_opacity=None, point\_opacity=None*)

**Parameters**

- **menu** (Optional[bool]) –
- **info** (Optional[bool]) –
- **show\_arrows** (Optional[bool]) –
- **point\_size** (Optional[float]) –
- **edge\_curvature** (Optional[float]) –
- **edge\_opacity** (Optional[float]) –
- **point\_opacity** (Optional[float]) –

`graphistry.pygraphistry.server` (*value=None*)

Get the hostname of the server or set the server using hostname or aliases. Also set via environment variable GRAPHISTRY\_HOSTNAME.

`graphistry.pygraphistry.settings` (*height=None, url\_params={}, render=None*)

`graphistry.pygraphistry.sso_get_token()`  
Get authentication token in SSO non-blocking mode

`graphistry.pygraphistry.sso_state(value=None)`  
Set or get the sso\_state when register/sso login.

`graphistry.pygraphistry.store_token_creds_in_memory(value=None)`  
Cache credentials for JWT token access. Default off due to not being safe.

`graphistry.pygraphistry strtobool(val)`

**Parameters** `val` (Any) –

**Return type** `bool`

`graphistry.pygraphistry.style(bg=None, fg=None, logo=None, page=None)`  
Creates a base plotter with some style settings.

For parameters, see `plotter.style`.

**Returns** `Plotter`

**Return type** *Plotter*

**Example**

```
import graphistry
graphistry.style(bg={'color': 'black'})
```

`graphistry.pygraphistry.switch_org(value)`

`graphistry.pygraphistry.tigergraph(protocol='http', server='localhost', web_port=14240,  
api_port=9000, db=None, user='tigergraph',  
pwd='tigergraph', verbose=False)`

Register Tigergraph connection setting defaults

**Parameters**

- **protocol** (*Optional[str]*) – Protocol used to contact the database.
- **server** (*Optional[str]*) – Domain of the database
- **web\_port** (*Optional[int]*) –
- **api\_port** (*Optional[int]*) –
- **db** (*Optional[str]*) – Name of the database
- **user** (*Optional[str]*) –
- **pwd** (*Optional[str]*) –
- **verbose** (*Optional[bool]*) – Whether to print operations

**Returns** `Plotter`

**Return type** *Plotter*

**Example: Standard**

```
import graphistry
tg = graphistry.tigergraph(protocol='https', server='acme.com', db='my_db',
↪ user='alice', pwd='tigergraph2')
```

`graphistry.pygraphistry.verify_token` (*token=None, fail\_silent=False*)  
Return True iff current or provided token is still valid

Return type `bool`

## 1.7 graphistry.arrow\_uploader module

```
class graphistry.arrow_uploader.ArrowUploader(server_base_path='http://nginx',  
                                              view_base_path='http://localhost',  
                                              name=None, description=None,  
                                              edges=None, nodes=None,  
                                              node_encodings=None,  
                                              edge_encodings=None, token=None,  
                                              dataset_id=None, metadata=None,  
                                              certificate_validation=True,  
                                              org_name=None)
```

Bases: `object`

Parameters **org\_name** (Optional[str]) –

**arrow\_to\_buffer** (*table*) –

Parameters **table** (Table) –

**cascade\_privacy\_settings** (*mode=None, notify=None, invited\_users=None,*  
 *mode\_action=None, message=None*)

Cascade:

- local (passed in)
- global
- hard-coded

Parameters

- **mode** (Optional[str]) –
- **notify** (Optional[bool]) –
- **invited\_users** (Optional[List]) –
- **mode\_action** (Optional[str]) –
- **message** (Optional[str]) –

property **certificate\_validation**

**create\_dataset** (*json*)

property **dataset\_id**

Return type `str`

property **description**

Return type `str`

property **edge\_encodings**

property **edges**

Return type `Table`

**g\_to\_edge\_bindings** (*g*)  
**g\_to\_edge\_encodings** (*g*)  
**g\_to\_node\_bindings** (*g*)  
**g\_to\_node\_encodings** (*g*)  
**login** (*username, password, org\_name=None*)  
**maybe\_bindings** (*g, bindings, base={}*)  
**maybe\_post\_share\_link** (*g*)  
 Skip if never called .privacy() Return True/False based on whether called  
 Return type `bool`  
**property metadata**  
**property name**  
 Return type `str`  
**property node\_encodings**  
**property nodes**  
 Return type `Table`  
**property org\_name**  
 Return type `Optional[str]`  
**pkey\_login** (*personal\_key\_id, personal\_key\_secret, org\_name=None*)  
**post** (*as\_files=True, memoize=True*)  
 Note: likely want to pair with self.maybe\_post\_share\_link(*g*)  
 Parameters  

- **as\_files** (`bool`) –
- **memoize** (`bool`) –

**post\_arrow** (*arr, graph\_type, opts=""*)  
 Parameters  

- **arr** (`Table`) –
- **graph\_type** (`str`) –
- **opts** (`str`) –

**post\_arrow\_generic** (*sub\_path, tok, arr, opts=""*)  
 Parameters  

- **sub\_path** (`str`) –
- **tok** (`str`) –
- **arr** (`Table`) –

 Return type `Response`  
**post\_edges\_arrow** (*arr=None, opts=""*)  
**post\_edges\_file** (*file\_path, file\_type='csv'*)  
**post\_file** (*file\_path, graph\_type='edges', file\_type='csv'*)

**post\_g** (*g, name=None, description=None*)

Warning: main post() does not call this

**post\_nodes\_arrow** (*arr=None, opts=""*)

**post\_nodes\_file** (*file\_path, file\_type='csv'*)

**post\_share\_link** (*obj\_pk, obj\_type='dataset', privacy=None*)

Set sharing settings. Any settings not passed here will cascade from PyGraphistry or defaults

#### Parameters

- **obj\_pk** (*str*) –
- **obj\_type** (*str*) –
- **privacy** (*Optional[dict]*) –

**refresh** (*token=None*)

**property server\_base\_path**

Return type *str*

**sso\_get\_token** (*state*)

Koa, 04 May 2022 Use state to get token

**sso\_login** (*org\_name=None, idp\_name=None*)

Koa, 04 May 2022 Get SSO login auth\_url or token

**property token**

Return type *str*

**verify** (*token=None*)

Return type *bool*

**property view\_base\_path**

Return type *str*

## 1.8 graphistry.ArrowFileUploader module

**class** graphistry.ArrowFileUploader.**ArrowFileUploader** (*uploader*)

Bases: *object*

Implement file API with focus on Arrow support

Memoization in this class is based on reference equality, while plotter is based on hash. That means the plotter resolves different-identity value matches, so by the time ArrowFileUploader compares, identities are unified for faster reference-based checks.

**Example: Upload files with per-session memoization** *uploader : ArrowUploader arr : pa.Table afu = ArrowFileUploader(uploader)*

*file1\_id = afu.create\_and\_post\_file(arr)[0] file2\_id = afu.create\_and\_post\_file(arr)[0]*

*assert file1\_id == file2\_id # memoizes by default (memory-safe: weak refs)*

**Example: Explicitly create a file and upload data for it** *uploader : ArrowUploader arr : pa.Table afu = ArrowFileUploader(uploader)*

*file1\_id = afu.create\_file() afu.post\_arrow(arr, file\_id)*

```
file2_id = afu.create_file() afu.post_arrow(arr, file_id)
```

```
assert file1_id != file2_id
```

**create\_and\_post\_file** (*arr*, *file\_id=None*, *file\_opts={}*, *upload\_url\_opts='erase=true'*, *memoize=True*)

Create file and upload data for it.

Default *upload\_url\_opts='erase=true'* throws exceptions on parse errors and deletes upload.

Default *memoize=True* skips uploading 'arr' when previously uploaded in current session

See File REST API for *file\_opts* (file create) and *upload\_url\_opts* (file upload)

#### Parameters

- **arr** (Table) –
- **file\_id** (Optional[str]) –
- **file\_opts** (dict) –
- **upload\_url\_opts** (str) –
- **memoize** (bool) –

**Return type** Tuple[str, dict]

**create\_file** (*file\_opts={}*)

Creates File and returns *file\_id* str.

#### Defaults:

- *file\_type*: 'arrow'

See File REST API for *file\_opts*

**Parameters** *file\_opts* (dict) –

**Return type** str

**post\_arrow** (*arr*, *file\_id*, *url\_opts='erase=true'*)

Upload new data to existing file id

Default *url\_opts='erase=true'* throws exceptions on parse errors and deletes upload.

See File REST API for *url\_opts* (file upload)

#### Parameters

- **arr** (Table) –
- **file\_id** (str) –
- **url\_opts** (str) –

**Return type** dict

**uploader:** Any = None

`graphistry.ArrowFileUploader.DF_TO_FILE_ID_CACHE: weakref.WeakKeyDictionary = <WeakKeyDict`

**NOTE:** Will switch to `pa.Table -> ...` when RAPIDS upgrades from pyarrow, which adds weakref support

**class** graphistry.ArrowFileUploader.MemoizedFileUpload (*file\_id*, *output*)

Bases: object

#### Parameters

```
    • file_id(str) -
    • output(dict) -
file_id:  str
output:  dict
class graphistry.ArrowFileUploader.WrappedTable(arr)
    Bases: object
        Parameters arr(Table) -
        arr:  pyarrow.lib.Table
graphistry.ArrowFileUploader.cache_arr(arr)
    Hold reference to most recent memoization entries Hack until RAPIDS supports Arrow 2.0, when pa.Table
    becomes weakly referenceable
```



## 2.1 versioneer module



## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`



## A

[add\(\)](#) (*graphistry.layout.utils.poset.Poset method*), 16  
[add\\_edge\(\)](#) (*graphistry.layout.graph.graph.Graph method*), 7  
[add\\_edge\(\)](#) (*graphistry.layout.graph.graphBase.GraphBase method*), 9  
[add\\_edges\(\)](#) (*graphistry.layout.graph.graph.Graph method*), 7  
[add\\_single\\_vertex\(\)](#) (*graphistry.layout.graph.graphBase.GraphBase method*), 9  
[add\\_vertex\(\)](#) (*graphistry.layout.graph.graph.Graph method*), 8  
[addStyle\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 20  
[addStyle\(\)](#) (*in module graphistry.pygraphistry*), 42  
[angle\\_between\\_vectors\(\)](#) (*in module graphistry.layout.utils.geometry*), 14  
[api\\_key\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 21  
[api\\_token\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 21  
[api\\_token\(\)](#) (*in module graphistry.pygraphistry*), 43  
[api\\_token\\_refresh\\_ms\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 21  
[api\\_version\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 21  
[arr](#) (*graphistry.ArrowFileUploader.WrappedTable attribute*), 68  
[arrange\(\)](#) (*graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout static method*), 11  
[arrow\\_to\\_buffer\(\)](#) (*graphistry.arrow\_uploader.ArrowUploader method*), 64  
[ArrowFileUploader](#) (*class in graphistry.ArrowFileUploader*), 66  
[ArrowUploader](#) (*class in graphistry.arrow\_uploader*), 64  
[attach\(\)](#) (*graphistry.layout.graph.edge.Edge method*), 7  
[authenticate\(\)](#) (*graphistry.pygraphistry.PyGraphistry*

*static method*), 21

## B

[bind\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 21  
[bind\(\)](#) (*in module graphistry.pygraphistry*), 43  
[bolt\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 21  
[bolt\(\)](#) (*in module graphistry.pygraphistry*), 43

## C

[cache\\_arr\(\)](#) (*in module graphistry.ArrowFileUploader*), 68  
[cascade\\_privacy\\_settings\(\)](#) (*graphistry.arrow\_uploader.ArrowUploader method*), 64  
[certificate\\_validation\(\)](#) (*graphistry.arrow\_uploader.ArrowUploader property*), 64  
[certificate\\_validation\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 22  
[chain\(\)](#) (*graphistry.compute.ComputeMixin.ComputeMixin method*), 3  
[client\\_protocol\\_hostname\(\)](#) (*graphistry.pygraphistry.PyGraphistry static method*), 22  
[client\\_protocol\\_hostname\(\)](#) (*in module graphistry.pygraphistry*), 43  
[collapse\(\)](#) (*graphistry.compute.ComputeMixin.ComputeMixin method*), 4  
[complement\(\)](#) (*graphistry.layout.graph.graphBase.GraphBase method*), 9  
[component\\_class](#) (*graphistry.layout.graph.graph.Graph attribute*), 8  
[compute\\_igraph\(\)](#) (*in module graphistry.plugins.igraph*), 17  
[ComputeMixin](#) (*class in graphistry.compute.ComputeMixin*), 3  
[connected\(\)](#) (*graphistry.layout.graph.graph.Graph method*), 8

`constant_function()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`contains__cmp__()` (`graphistry.layout.utils.poset.Poset` method), 16  
`contract()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`copy()` (`graphistry.layout.utils.poset.Poset` method), 16  
`cosmos()` (`graphistry.pygraphistry.PyGraphistry` static method), 22  
`cosmos()` (in module `graphistry.pygraphistry`), 43  
`create_and_post_file()` (`graphistry.ArrowFileUploader.ArrowFileUploader` method), 67  
`create_dataset()` (`graphistry.arrow_uploader.ArrowUploader` method), 64  
`create_dummies()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` method), 12  
`create_file()` (`graphistry.ArrowFileUploader.ArrowFileUploader` method), 67  
`crossings` (`graphistry.layout.utils.layer.Layer` attribute), 15  
`ctrls` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` attribute), 12  
`cypher()` (`graphistry.pygraphistry.PyGraphistry` static method), 22  
`cypher()` (in module `graphistry.pygraphistry`), 44  
**D**  
`data` (`graphistry.layout.graph.edge.Edge` attribute), 7  
`dataset_id()` (`graphistry.arrow_uploader.ArrowUploader` property), 64  
`deepcopy()` (`graphistry.layout.utils.poset.Poset` method), 16  
`default()` (`graphistry.pygraphistry.NumpyJSONEncoder` method), 20  
`deg_avg()` (`graphistry.layout.graph.graph.Graph` method), 8  
`deg_avg()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`deg_max()` (`graphistry.layout.graph.graph.Graph` method), 8  
`deg_max()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`deg_min()` (`graphistry.layout.graph.graph.Graph` method), 8  
`deg_min()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`degree` (`graphistry.layout.graph.edgeBase.EdgeBase` attribute), 7  
`degree()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`description()` (`graphistry.arrow_uploader.ArrowUploader` property), 64  
`description()` (`graphistry.pygraphistry.PyGraphistry` static method), 23  
`description()` (in module `graphistry.pygraphistry`), 44  
`detach()` (`graphistry.layout.graph.edge.Edge` method), 7  
`detach()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`DF_TO_FILE_ID_CACHE` (in module `graphistry.ArrowFileUploader`), 67  
`dft()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`difference()` (`graphistry.layout.utils.poset.Poset` method), 16  
`dirvctrl()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`dirvctrl()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` property), 12  
`dirvctrl()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` property), 12  
`dirvh()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` property), 12  
`dirvstep()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` method), 12  
`drop_graph()` (`graphistry.pygraphistry.PyGraphistry` static method), 23  
`drop_graph()` (in module `graphistry.pygraphistry`), 44  
`drop_nodes()` (`graphistry.compute.ComputeMixin.ComputeMixin` method), 4  
`dummyctrl()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` method), 12  
`DummyVertex` (class in `graphistry.layout.utils.dummyVertex`), 14  
**E**  
`e_dir()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`e_from()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`e_in()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`e_out()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`e_to()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`e_with()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`Edge` (class in `graphistry.layout.graph.edge`), 6  
`edge_encodings()` (`graphistry.arrow_uploader.ArrowUploader` property), 64  
`EdgeBase` (class in `graphistry.layout.graph.edgeBase`), 7

edges() (graphistry.arrow\_uploader.ArrowUploader property), 64

edges() (graphistry.layout.graph.graph.Graph method), 8

edges() (graphistry.layout.graph.graphBase.GraphBase method), 9

edges() (graphistry.pygraphistry.PyGraphistry static method), 23

edges() (in module graphistry.pygraphistry), 44

EdgeViewer (class in graphistry.layout.utils.routing), 16

encode\_edge\_badge() (graphistry.pygraphistry.PyGraphistry static method), 23

encode\_edge\_badge() (in module graphistry.pygraphistry), 45

encode\_edge\_color() (graphistry.pygraphistry.PyGraphistry static method), 23

encode\_edge\_color() (in module graphistry.pygraphistry), 45

encode\_edge\_icon() (graphistry.pygraphistry.PyGraphistry static method), 24

encode\_edge\_icon() (in module graphistry.pygraphistry), 46

encode\_point\_badge() (graphistry.pygraphistry.PyGraphistry static method), 25

encode\_point\_badge() (in module graphistry.pygraphistry), 47

encode\_point\_color() (graphistry.pygraphistry.PyGraphistry static method), 25

encode\_point\_color() (in module graphistry.pygraphistry), 47

encode\_point\_icon() (graphistry.pygraphistry.PyGraphistry static method), 26

encode\_point\_icon() (in module graphistry.pygraphistry), 48

encode\_point\_size() (graphistry.pygraphistry.PyGraphistry static method), 27

encode\_point\_size() (in module graphistry.pygraphistry), 49

ensure\_root\_is\_vertex() (graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout static method), 12

eps() (graphistry.layout.graph.graph.Graph method), 8

eps() (graphistry.layout.graph.graphBase.GraphBase method), 9

## F

feedback (graphistry.layout.graph.edge.Edge attribute), 7

file\_id (graphistry.ArrowFileUploader.MemoizedFileUpload attribute), 68

filter\_edges\_by\_dict() (graphistry.compute.ComputeMixin.ComputeMixin method), 4

filter\_nodes\_by\_dict() (graphistry.compute.ComputeMixin.ComputeMixin method), 4

find\_nearest\_layer() (graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout method), 13

from\_cugraph() (graphistry.pygraphistry.PyGraphistry static method), 28

from\_cugraph() (in module graphistry.pygraphistry), 49

from\_igraph() (graphistry.pygraphistry.PyGraphistry static method), 28

from\_igraph() (in module graphistry.plugins.igraph), 18

from\_igraph() (in module graphistry.pygraphistry), 50

## G

g\_to\_edge\_bindings() (graphistry.arrow\_uploader.ArrowUploader method), 65

g\_to\_edge\_encodings() (graphistry.arrow\_uploader.ArrowUploader method), 65

g\_to\_node\_bindings() (graphistry.arrow\_uploader.ArrowUploader method), 65

g\_to\_node\_encodings() (graphistry.arrow\_uploader.ArrowUploader method), 65

get() (graphistry.layout.utils.poset.Poset method), 16

get\_degrees() (graphistry.compute.ComputeMixin.ComputeMixin method), 4

get\_indegrees() (graphistry.compute.ComputeMixin.ComputeMixin method), 5

get\_outdegrees() (graphistry.compute.ComputeMixin.ComputeMixin method), 5

get\_scs\_with\_feedback() (graphistry.layout.graph.graphBase.GraphBase method), 9

get\_topological\_levels() (graphistry.compute.ComputeMixin.ComputeMixin method), 5

get\_vertex\_from\_data() (graphistry.layout.graph.graph.Graph method), 8

```

get_vertices_count()
    (graphistry.layout.graph.graph.Graph
     method), 8
Graph (class in graphistry.layout.graph.graph), 7
graph() (graphistry.pygraphistry.PyGraphistry static
        method), 28
graph() (in module graphistry.pygraphistry), 50
graph_from_pandas()
    (graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout
     static method), 13
GraphBase (class
           graphistry.layout.graph.graphBase), 8
graphistry.arrow_uploader
    module, 64
graphistry.ArrowFileUploader
    module, 66
graphistry.compute
    module, 6
graphistry.compute.ComputeMixin
    module, 3
graphistry.layout
    module, 17
graphistry.layout.gib
    module, 6
graphistry.layout.graph
    module, 11
graphistry.layout.graph.edge
    module, 6
graphistry.layout.graph.edgeBase
    module, 7
graphistry.layout.graph.graph
    module, 7
graphistry.layout.graph.graphBase
    module, 8
graphistry.layout.graph.vertex
    module, 10
graphistry.layout.graph.vertexBase
    module, 10
graphistry.layout.sugiyama
    module, 14
graphistry.layout.sugiyama.sugiyamaLayout
    module, 11
graphistry.layout.utils
    module, 17
graphistry.layout.utils.dummyVertex
    module, 14
graphistry.layout.utils.geometry
    module, 14
graphistry.layout.utils.layer
    module, 15
graphistry.layout.utils.layoutVertex
    module, 15
graphistry.layout.utils.poset
    module, 16
graphistry.layout.utils.rectangle
    module, 16
graphistry.layout.utils.routing
    module, 16
graphistry.plotter
    module, 20
graphistry.plugins
    module, 20
graphistry.plugins.igraph
    module, 17
graphistry.plugins_types
    module, 20
graphistry.plugins_types.cugraph_types
    module, 20
graphistry.pygraphistry
    module, 20
gremlin() (graphistry.pygraphistry.PyGraphistry
          static method), 28
gremlin() (in module graphistry.pygraphistry), 50
gremlin_client() (graphistry.pygraphistry.PyGraphistry
                 static method), 28
gremlin_client() (in module
                 graphistry.pygraphistry), 50
gsql() (graphistry.pygraphistry.PyGraphistry static
       method), 29
gsql() (in module graphistry.pygraphistry), 50
gsql_endpoint() (graphistry.pygraphistry.PyGraphistry
                static method), 30
gsql_endpoint() (in module
                graphistry.pygraphistry), 52

```

## H

```

has_cycles() (graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout
            static method), 13
hop() (graphistry.compute.ComputeMixin.ComputeMixin
      method), 5
hypergraph() (graphistry.pygraphistry.PyGraphistry
             static method), 31
hypergraph() (in module graphistry.pygraphistry),
             52

```

## I

```

idp_name() (graphistry.pygraphistry.PyGraphistry
          static method), 33
idp_name() (in module graphistry.pygraphistry), 55
index() (graphistry.layout.graph.vertex.Vertex prop-
        erty), 10
index() (graphistry.layout.utils.poset.Poset method),
        16
infer_labels() (graphistry.pygraphistry.PyGraphistry
              static method), 33
infer_labels() (in module
              graphistry.pygraphistry), 55

```



[initialize\(\)](#) ([graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout](#) [method](#)), 13  
[inner\(\)](#) ([graphistry.layout.utils.dummyVertex.DummyVertex](#) [method](#)), 14  
[intersection\(\)](#) ([graphistry.layout.utils.poset.Poset](#) [method](#)), 16  
[issubset\(\)](#) ([graphistry.layout.utils.poset.Poset](#) [method](#)), 16  
[issuperset\(\)](#) ([graphistry.layout.utils.poset.Poset](#) [method](#)), 16  
[MemoizedFileUpload](#) (class in [graphistry.ArrowFileUploader](#)), 67  
[metadata\(\)](#) ([graphistry.arrow\\_uploader.ArrowUploader](#) [property](#)), 65  
[module](#)

## K

[keep\\_nodes\(\)](#) ([graphistry.compute.ComputeMixin.ComputeMixin](#) [method](#)), 5

## L

[Layer](#) (class in [graphistry.layout.utils.layer](#)), 15  
[layers](#) ([graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout](#) [attribute](#)), 13  
[layout](#) ([graphistry.layout.utils.layer.Layer](#) [attribute](#)), 15  
[layout\(\)](#) ([graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout](#) [method](#)), 13  
[layout\\_edges\(\)](#) ([graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout](#) [method](#)), 13  
[layout\\_igraph\(\)](#) (in [module](#) [graphistry.plugins.igraph](#)), 18  
[layout\\_settings\(\)](#) ([graphistry.pygraphistry.PyGraphistry](#) [static method](#)), 33  
[layout\\_settings\(\)](#) (in [module](#) [graphistry.pygraphistry](#)), 55  
[LayoutVertex](#) (class in [graphistry.layout.utils.layoutVertex](#)), 15  
[layoutVertices](#) ([graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout](#) [attribute](#)), 13  
[leaves\(\)](#) ([graphistry.layout.graph.graphBase.GraphBase](#) [method](#)), 9  
[lines\\_intersection\(\)](#) (in [module](#) [graphistry.layout.utils.geometry](#)), 14  
[login\(\)](#) ([graphistry.arrow\\_uploader.ArrowUploader](#) [method](#)), 65  
[login\(\)](#) ([graphistry.pygraphistry.PyGraphistry](#) [static method](#)), 34  
[login\(\)](#) (in [module](#) [graphistry.pygraphistry](#)), 56  
[lower](#) ([graphistry.layout.utils.layer.Layer](#) [attribute](#)), 15

## M

[materialize\\_nodes\(\)](#) ([graphistry.compute.ComputeMixin.ComputeMixin](#) [method](#)), 6  
[matrix\(\)](#) ([graphistry.layout.graph.graphBase.GraphBase](#) [method](#)), 9

[graphistry.arrow\\_uploader](#), 64  
[graphistry.ArrowFileUploader](#), 66  
[graphistry.compute](#), 6  
[graphistry.compute.ComputeMixin](#), 3  
[graphistry.layout](#), 17  
[graphistry.layout.gib](#), 6  
[graphistry.layout.graph](#), 11  
[graphistry.layout.graph.edge](#), 6  
[graphistry.layout.graph.edgeBase](#), 7  
[graphistry.layout.graph.graph](#), 7  
[graphistry.layout.graph.graphBase](#), 8  
[graphistry.layout.graph.vertex](#), 10  
[graphistry.layout.graph.vertexBase](#), 10  
[graphistry.layout.sugiyama](#), 14  
[graphistry.layout.sugiyama.sugiyamaLayout](#), 11  
[graphistry.layout.utils](#), 17  
[graphistry.layout.utils.dummyVertex](#), 14  
[graphistry.layout.utils.geometry](#), 14  
[graphistry.layout.utils.layer](#), 15  
[graphistry.layout.utils.layoutVertex](#), 15  
[graphistry.layout.utils.poset](#), 16  
[graphistry.layout.utils.rectangle](#), 16  
[graphistry.layout.utils.routing](#), 16  
[graphistry.plotter](#), 20  
[graphistry.plugins](#), 20  
[graphistry.plugins.igraph](#), 17  
[graphistry.plugins\\_types](#), 20  
[graphistry.plugins\\_types.cugraph\\_types](#), 20  
[graphistry.pygraphistry](#), 20

## N

[N\(\)](#) ([graphistry.layout.graph.graph.Graph](#) [method](#)), 7  
[N\(\)](#) ([graphistry.layout.graph.graphBase.GraphBase](#) [method](#)), 9  
[name\(\)](#) ([graphistry.arrow\\_uploader.ArrowUploader](#) [property](#)), 65  
[name\(\)](#) ([graphistry.pygraphistry.PyGraphistry](#) [static method](#)), 34

`name()` (in module `graphistry.pygraphistry`), 56  
`neighbors()` (`graphistry.layout.graph.vertexBase.VertexBase` method), 10  
`neighbors()` (`graphistry.layout.utils.dummyVertex.DummyVertex` method), 14  
`neighbors()` (`graphistry.layout.utils.layer.Layer` method), 15  
`neptune()` (`graphistry.pygraphistry.PyGraphistry` static method), 34  
`neptune()` (in module `graphistry.pygraphistry`), 56  
`new_point_at_distance()` (in module `graphistry.layout.utils.geometry`), 14  
`nextlayer()` (`graphistry.layout.utils.layer.Layer` method), 15  
`node_encodings()` (`graphistry.arrow_uploader.ArrowUploader` property), 65  
`nodes()` (`graphistry.arrow_uploader.ArrowUploader` property), 65  
`nodes()` (`graphistry.pygraphistry.PyGraphistry` static method), 35  
`nodes()` (in module `graphistry.pygraphistry`), 57  
`nodexl()` (`graphistry.pygraphistry.PyGraphistry` static method), 36  
`nodexl()` (in module `graphistry.pygraphistry`), 58  
`norm()` (`graphistry.layout.graph.graph.Graph` method), 8  
`norm()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`not_implemented_thunk()` (`graphistry.pygraphistry.PyGraphistry` static method), 36  
`NumpyJSONEncoder` (class in `graphistry.pygraphistry`), 20

**O**

`order()` (`graphistry.layout.graph.graph.Graph` method), 8  
`order()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`order()` (`graphistry.layout.utils.layer.Layer` method), 15  
`ordering_step()` (`graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout` method), 13  
`org_name()` (`graphistry.arrow_uploader.ArrowUploader` property), 65  
`org_name()` (`graphistry.pygraphistry.PyGraphistry` static method), 36  
`org_name()` (in module `graphistry.pygraphistry`), 58  
`output` (`graphistry.ArrowFileUploader.MemoizedFileUploader` attribute), 68

**P**

`partition()` (`graphistry.layout.graph.graphBase.GraphBase` method), 9  
`path()` (`graphistry.layout.graph.graph.Graph` method), 8  
`path()` (`graphistry.layout.graph.graphBase.GraphBase` method), 36  
`personal_key_id()` (`graphistry.pygraphistry.PyGraphistry` static method), 36  
`personal_key_id()` (in module `graphistry.pygraphistry`), 58  
`personal_key_secret()` (`graphistry.pygraphistry.PyGraphistry` static method), 37  
`personal_key_secret()` (in module `graphistry.pygraphistry`), 58  
`upload()` (`graphistry.pygraphistry.PyGraphistry` static method), 37  
`pipe()` (in module `graphistry.pygraphistry`), 58  
`pkey_login()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`pkey_login()` (`graphistry.pygraphistry.PyGraphistry` static method), 37  
`Plotter` (class in `graphistry.plotter`), 20  
`Poset` (class in `graphistry.layout.utils.poset`), 16  
`post()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_arrow()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_arrow()` (`graphistry.ArrowFileUploader.ArrowFileUploader` method), 67  
`post_arrow_generic()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_edges_arrow()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_edges_file()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_file()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_g()` (`graphistry.arrow_uploader.ArrowUploader` method), 65  
`post_nodes_arrow()` (`graphistry.arrow_uploader.ArrowUploader` method), 66  
`post_nodes_file()` (`graphistry.arrow_uploader.ArrowUploader` method), 66  
`post_share_link()` (`graphistry.arrow_uploader.ArrowUploader` method), 66  
`prevlayer()` (`graphistry.layout.utils.layer.Layer` method), 15  
`privacy()` (`graphistry.pygraphistry.PyGraphistry`

- static method), 37
- privacy() (in module graphistry.pygraphistry), 59
- protocol() (graphistry.pygraphistry.PyGraphistry static method), 39
- protocol() (in module graphistry.pygraphistry), 60
- prune\_self\_edges() (graphistry.compute.ComputeMixin.ComputeMixin method), 6
- PyGraphistry (class in graphistry.pygraphistry), 20
- ## R
- Rectangle (class in graphistry.layout.utils.rectangle), 16
- rectangle\_point\_intersection() (in module graphistry.layout.utils.geometry), 14
- refresh() (graphistry.arrow\_uploader.ArrowUploader method), 66
- refresh() (graphistry.pygraphistry.PyGraphistry static method), 39
- refresh() (in module graphistry.pygraphistry), 60
- register() (graphistry.pygraphistry.PyGraphistry static method), 39
- register() (in module graphistry.pygraphistry), 60
- relogin() (graphistry.pygraphistry.PyGraphistry method), 41
- remove() (graphistry.layout.utils.poset.Poset method), 16
- remove\_edge() (graphistry.layout.graph.graph.Graph method), 8
- remove\_edge() (graphistry.layout.graph.graphBase.GraphBase method), 9
- remove\_vertex() (graphistry.layout.graph.graph.Graph method), 8
- remove\_vertex() (graphistry.layout.graph.graphBase.GraphBase method), 9
- roots() (graphistry.layout.graph.graphBase.GraphBase method), 9
- route\_with\_lines() (in module graphistry.layout.utils.routing), 16
- route\_with\_rounded\_corners() (in module graphistry.layout.utils.routing), 16
- route\_with\_splines() (in module graphistry.layout.utils.routing), 16
- ## S
- scene\_settings() (graphistry.pygraphistry.PyGraphistry static method), 41
- scene\_settings() (in module graphistry.pygraphistry), 62
- server() (graphistry.pygraphistry.PyGraphistry static method), 41
- server() (in module graphistry.pygraphistry), 62
- server\_base\_path() (graphistry.arrow\_uploader.ArrowUploader property), 66
- set\_bolt\_driver() (graphistry.pygraphistry.PyGraphistry static method), 41
- set\_coordinates() (graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout method), 13
- set\_round\_corner() (in module graphistry.layout.utils.geometry), 14
- set\_topological\_coordinates() (graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout method), 13
- setcurve() (in module graphistry.layout.utils.geometry), 14
- setpath() (graphistry.layout.utils.routing.EdgeViewer method), 16
- settings() (graphistry.pygraphistry.PyGraphistry static method), 41
- settings() (in module graphistry.pygraphistry), 62
- setup() (graphistry.layout.utils.layer.Layer method), 15
- size\_median() (in module graphistry.layout.utils.geometry), 14
- spans() (graphistry.layout.graph.graphBase.GraphBase method), 10
- sso\_get\_token() (graphistry.arrow\_uploader.ArrowUploader method), 66
- sso\_get\_token() (graphistry.pygraphistry.PyGraphistry static method), 41
- sso\_get\_token() (in module graphistry.pygraphistry), 62
- sso\_login() (graphistry.arrow\_uploader.ArrowUploader method), 66
- sso\_login() (graphistry.pygraphistry.PyGraphistry static method), 41
- sso\_state() (graphistry.pygraphistry.PyGraphistry static method), 41
- sso\_state() (in module graphistry.pygraphistry), 63
- store\_token\_creds\_in\_memory() (graphistry.pygraphistry.PyGraphistry static method), 41
- store\_token\_creds\_in\_memory() (in module graphistry.pygraphistry), 63
- strtobool() (in module graphistry.pygraphistry), 63
- style() (graphistry.pygraphistry.PyGraphistry static method), 42
- style() (in module graphistry.pygraphistry), 63
- SugiyamaLayout (class in graphistry.layout.sugiyama.sugiyamaLayout), 11
- switch\_org() (graphistry.pygraphistry.PyGraphistry static method), 42
- switch\_org() (in module graphistry.pygraphistry), 63

`symmetric_difference()`  
(*graphistry.layout.utils.poset.Poset method*), 16

## T

`tangents()` (in module *graphistry.layout.utils.geometry*), 14  
`tigergraph()` (*graphistry.pygraphistry.PyGraphistry static method*), 42  
`tigergraph()` (in module *graphistry.pygraphistry*), 63  
`to_igraph()` (in module *graphistry.plugins.igraph*), 19  
`token()` (*graphistry.arrow\_uploader.ArrowUploader property*), 66

## U

`union()` (*graphistry.layout.utils.poset.Poset method*), 16  
`union_update()` (*graphistry.layout.graph.graphBase.GraphBase method*), 10  
`update()` (*graphistry.layout.utils.poset.Poset method*), 16  
`uploader` (*graphistry.ArrowFileUploader.ArrowFileUploader attribute*), 67  
`upper` (*graphistry.layout.utils.layer.Layer attribute*), 15

## V

`verify()` (*graphistry.arrow\_uploader.ArrowUploader method*), 66  
`verify_token()` (*graphistry.pygraphistry.PyGraphistry static method*), 42  
`verify_token()` (in module *graphistry.pygraphistry*), 63  
`Vertex` (class in *graphistry.layout.graph.vertex*), 10  
`VertexBase` (class in *graphistry.layout.graph.vertexBase*), 10  
`vertices()` (*graphistry.layout.graph.graph.Graph method*), 8  
`vertices()` (*graphistry.layout.graph.graphBase.GraphBase method*), 10  
`view_base_path()` (*graphistry.arrow\_uploader.ArrowUploader property*), 66

## W

`w` (*graphistry.layout.graph.edge.Edge attribute*), 7  
`WrappedTable` (class in *graphistry.ArrowFileUploader*), 68

## X

`xspace` (*graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout attribute*), 13

## Y

`yspace` (*graphistry.layout.sugiyama.sugiyamaLayout.SugiyamaLayout attribute*), 13